

16000025

ATyS C25ATS Controller

Strong points

- Flexible space saving
- Cost-effective
- Fast commissioning & testing

General characteristics

- Self-powered from sensing.
- Voltage supply range (184 - 300 VAC).
- 24 VDC aux power supply (for optional use).
- Main/Main or Main/Genset networks.
- Fixed I/Os.
- RS485 Modbus communication.
- Voltage sensing on all phases.
- Three-phase + Neutral & Single-phase + Neutral networks.
- Phase rotation checking.
- Door or DIN rail mounting.

Compliance with standards

- IEC 61010-2-201
- IEC 60947-6-1
- GB/T 14048.11 Annex C

Link to the reference

ATyS C25 is an entry level ATSE controller with communications. It can be used to pilot a remotely operated transfer switch, such as ATyS r, ATyS S and ATyS d M, as well as contactors. ATyS C25 ensure the automatic or remotely controlled transfer from one source to another with fixed timers and thresholds.

Classification

UNSPSC	39122331
ETIM Class	EC002498
IGCC	5367

Commerce

Effective date	2019-01-29
Country of origin	CN

ETIM - Technical features

Type of accessory/spare part	Communication and measuring function
Accessory	Yes
Spare part	No

Logistics

GTIN/EAN	3596033086830
Customs number	8537109199
Price unit	PC
Weight of the packing unit	1.095
Length of the packing unit	0.15
Width of the packing unit	0.125
Depth of the packing unit	0.17

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Model	Atys C25
-------	----------