



ABB

Genuine products

Dedicated
Support

Doorstep Delivery

[eMart](#)

Share with your friends



Automation & Control

A16-40-00 400-415V 50Hz / 415-440V 60Hz Contactor

Out of stock

Upon Request

Product Id#: 1SBL181201R8600

[Be the first to review this product](#)

A16 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Enquire Now

More about A16-40-00 400-415V 50Hz / 415-440V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	4
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour, AC-3 1200 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 30 ampere

Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 8 2 volt - ampere, Holding at Max. Rated Control Circuit Voltage 60 Hz 8 2 volt - ampere, Pull-in at Max. Rated Control Circuit Voltage 50 Hz 70 volt - ampere, Pull- in at Max. Rated Control Circuit Volta
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NO Contact Opening 4 ... 11 millisecond, Between Coil Energization and NO Contact Closing 10 ... 26 millisecond
Rated Control Circuit Voltage (Uc)	50 Hz 400-415V; 60 Hz 415-440V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 4 KWT, (380 / 400 V) 7.5 KWT, (415 V) 9 KWT, (440 V) 9 KWT, (500 V) 9 KWT, (690 V) 9 KWT
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 17 ampere, (380 / 400 V) 55 °C 17 ampere, (415 V) 55 °C 17 ampere, (440 V) 55 °C 16 ampere, (500 V) 55 °C 14 ampere, (690 V) 55 °C 10 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 30 ampere, (690 V) 55 °C 27 ampere, (690 V) 70 °C 23 ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Frequency Limits	25 ... 400 hertz
Package Width	78 millimetre
Package Length	76 millimetre
Package Height	47 millimetre
Invoice Description	A16-40-00 400-415V 50Hz / 415-440V 60Hz Contactor
Product Range	A Contactors
Package Gross Weight	0.34 kilogram
Extended Product Type	A16-40-00 400-415V 50Hz / 415-440V 60Hz
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 degree Celsius, Near Contactor for Operation in Free Air (Uc) -40 ... +70 degree Celsius, Near Contactor for Operation in Free Air (0.85 ... 1.1 Uc) -40 ... +55 degree Celsius
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

Enquire Now

[Download](#)

[Reviews](#)



Recently Viewed

 <p><u>A16-22-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL181501R8600 Out of Stock</p>	 <p><u>A26-22-00 220-230V 50Hz / 230-240V 60Hz Contactor</u> 1SBL241501R8000 ₹2,036.09</p>	 <p><u>A26-22-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL241501R8600 Out of Stock</p>	 <p><u>A45-40-00 110V 50Hz / 110-126V 60Hz Contactor</u> 1SBL331201R8400 ₹4,217.00</p>
---	---	--	---

☐ [Write to Us](#)

COMPANY

INFORMATION

PAYMENT METHODS

1800 420 0707
@ contactabb.in@abb.com
(Only for India Inquiries)

AboutSell Our BlogsExchange and Privacy Terms How to create a
Us With Sellers Returns Policy Policy of Use Company Account FAQ

Disha - Plot No.5 & 6, 2nd Stage, Peenya
Industrial Area IV, Peenya 560058,
Bangalore, Karnataka, India.

 [Facebook](#)  [Twitter](#)
 [Linkedin](#)  [Youtube](#)

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

Enquire Now

