

[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > A26-40-00 220-230V 50Hz / 230-240V 60Hz Contactor

Genuine products

Dedicated
Support

Doorstep Delivery

**ADD TO WISH LIST**
Share with your friends[eMart](#)

Enquire Now

Automation & Control

A26-40-00 220-230V 50Hz / 230-240V 60Hz Contactor

₹1220.90 + ₹219.76 (GST 18%)

- 1 +

Buy Now

Add to Cart

More Offers available from [8 sellers](#) starting at
INR. 1440.66

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL241201R8000

[Be the first to review this product](#)

Sold and delivered by **PIGEON AGENCY**

A26 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

More about A26-40-00 220-230V 50Hz / 230-240V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	4
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40
Coil Consumption	Holding at Max. Rated Control Circuit Voltage Holding at Max. Rated Control Circuit Voltage Pull-in at Max. Rated Control Circuit Voltage 5 Pull-in at Max. Rated Control Circuit Vo
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NO Contact millisecond, Between Coil Energization and NO millisecond
Rated Control Circuit Voltage (Uc)	50 Hz 220-230V; 60 Hz 230-240V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 6.5 KWT, (380 / 400 V) 11 k V) 15 KWT, (500 V) 15 KWT

Enquire Now



Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 26 ampere, (380 / 400 V) 55 °C 26 ampere, (440 V) 55 °C 26 ampere, (690 V) 55 °C 17 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 45 ampere, (690 V) 55 °C 40 ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Frequency Limits	25 ... 400 hertz
Package Width	101 millimetre
Package Length	115 millimetre
Package Height	61 millimetre
Invoice Description	A26-40-00 220-230V 50Hz / 230-240V 60Hz Contactor
Product Range	A Contactors
Package Gross Weight	0.61 kilogram
Extended Product Type	A26-40-00 220-230V 50Hz / 230-240V 60Hz Contactor
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Close to Contactor for Operation in Free Air (Uc) -40 ... +80 °C Close to Contactor for Operation in Free Air (0.85 Ie) -10 ... +11 °C Celsius
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited




[Download](#)

[Offers](#)

[Reviews](#)



Recently Viewed

 <p><u>A26-40-00 24V 50Hz / 24V 60Hz</u> <u>Contactor</u> 1SBL241201R8100 Out of Stock</p>	 <p><u>A26-40-00 400-415V 50Hz / 415-440V 60Hz</u> <u>Contactor</u> 1SBL241201R8600 Out of Stock</p>	 <p><u>A26-22-00 110V 50Hz / 110-120V</u> <u>60Hz</u> 1SBL241501R8400 ₹2,508.00</p>	<u>A26</u>
--	--	--	------------


☐ Write to Us


1800 420 0707


@ contactabb.in@abb.com


(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya
Industrial Area IV, Peenya 560058,
Bangalore, Karnataka, India.

 [Facebook](#)

 [Twitter](#)

 [Linkedin](#)

 [Youtube](#)

COMPANY

INFORMATION

About Us

Sell With Us

Our Sellers

Blogs

Exchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

Enquire Now

