

[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > A26-22-00 110V 50Hz[♥ ADD TO WISH LIST](#)

Share with your friends

Automation & Control
ABB

Genuine products

Dedicated
Support

Doorstep Delivery

Enquire Now

^{eMart}
**A26-22-00 110V 50Hz / 110-120V
60Hz**

₹2125.42 + ₹382.58 (GST 18%)

- 1 +

Buy Now

Add to Cart

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL241501R8400

[Be the first to review this product](#)Sold and delivered by **Micronova Impex Pvt Ltd**

A26 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 2 N.O. + 2 N.C. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

More about A26-22-00 110V 50Hz / 110-120V 60Hz

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	2
Number of Main Contacts NC	2
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40
Coil Consumption	Holding at Max. Rated Control Circuit Voltage Holding at Max. Rated Control Circuit Voltage Pull-in at Max. Rated Control Circuit Voltage 5 Pull-in at Max. Rated Control Circuit Vo
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NC Contact millisecond, Between Coil De-energization and ... 11 millisecond, Between Coil Energization ar ... 18 millisecond, Between Coil Energization a
Rated Control Circuit Voltage (Uc)	50 Hz 110V; 60 Hz 110-120V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3

Enquire Now



Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 45 ampere, (690 V) 55 °C 40 am; ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Frequency Limits	25 ... 400 hertz
Package Width	101 millimetre
Package Length	115 millimetre
Package Height	61 millimetre
Invoice Description	CONTACTOR
Product Range	A Contactors
Package Gross Weight	0.61 kilogram
Extended Product Type	A26-22-00 110V 50Hz / 110-120V 60Hz
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 deg Contactor for Operation in Free Air (Uc) -40 ... Contactor for Operation in Free Air (0.85 ... 1.1 Celsius
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

[Download](#)

[Offers](#)

[Reviews](#)

Recently Viewed




 <p><u>A26-22-00 24V 50Hz / 24V 60Hz Contactor</u> 1SBL241501R8100 ₹2,914.00</p>	 <p><u>A50-40-00 220-230V 50Hz / 230-240V 60Hz Contactor</u> 1SBL351201R8000 ₹6,012.34</p>	 <p><u>AL9-30-01 24V DC Contactor</u> 1SBL143001R8101 ₹1,185.31</p>	<u>AL</u>
--	---	--	-----------


☐ Write to Us


1800 420 0707


@ contactabb.in@abb.com
(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya
Industrial Area IV, Peenya 560058,
Bangalore, Karnataka, India.

 [Facebook](#)

 [Twitter](#)

 [Linkedin](#)

 [Youtube](#)

COMPANY

INFORMATION

About Us

Sell Our Us

Blogs

Exchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

Enquire Now

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bang