



♥ **ADD TO WISH LIST**

Share with your friends

Genuine products

Dedicated
Support

Doorstep Delivery



eMart

Automation & Control

A30-30-01 400-415V 50Hz / 415-440V 60Hz Contactor

₹2079.00 + ₹374.22 (GST 18%)

- 1 +

Buy Now

Add to Cart

More Offers available from [5 sellers](#) starting at
INR. 2453.22

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL281001R8601

[Be the first to review this product](#)

Sold and delivered by **EBASCO MARKETING**

A30 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Enquire Now

More about A30-30-01 400-415V 50Hz / 415-440V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)

Not for Retail Sale



Number of Main Contacts NO	3
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour, AC-3 1200 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-5-1, q = 40 °C 16 ampere, acc. to IEC 60947-4-1, Open Contactors q = 40 °C 65 ampere
Coil Consumption	Average Holding Value 50 / 60 Hz 12.3 volt - ampere, Average Pull-in Value 50 Hz 125 volt - ampere, Average Pull-in Value 60 Hz 120 volt - ampere
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 14 millisecond, Between Coil De-energization and NO Contact Opening 4 ... 11 millisecond, Between Coil Energization and NC Contact Opening 6 ... 18 millisecond, Between Coil Energization and NO Con
Rated Control Circuit Voltage (Uc)	50 Hz 400-415V; 60 Hz 415-440V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-6b (Pe)	(230 / 240 V) 40 °C, 50 / 60 Hz 13 KVR, (230 / 240 V) 55 °C, 50 / 60 Hz 13 KVR, (230 / 240 V) 70 °C, 50 / 60 Hz 11 KVR, (400 / 415 V) 40 °C, 50 / 60 Hz 22 KVR, (400 / 415 V) 70 °C, 50 / 60 Hz 18.5 KVR, (400 / 415 V) 55 °C, 50 / 60 Hz 22 KVR, (440 V) 40 °C
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 9 KWT, (380 / 400 V) 15 KWT, (415 V) 15 KWT, (440 V) 18.5 KWT, (500 V) 18.5 KWT, (690 V) 18.5 KWT
Rated Operational Current DC-13 (Ie)	(125 V) 1.1 / 138 ampere, (24 V) 6 / 144 ampere, (250 V) 0.55 / 138 ampere, (48 V) 2.8 / 134 ampere, (72 V) 2 / 144 ampere
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 33 ampere, (380 / 400 V) 55 °C 32 ampere, (415 V) 55 °C 32 ampere, (440 V) 55 °C 32 ampere, (500 V) 55 °C 28 ampere, (690 V) 55 °C 21 ampere
Rated Operational Current AC-15 (Ie)	(220 / 240 V) 4 ampere, (24 / 127 V) 6 ampere, (380 / 440 V) 3 ampere, (500 V) 2 ampere, (690 V) 2 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 55 ampere, (690 V) 55 °C 55 ampere, (690 V) 70 °C 39 ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x Ie AC-15
Rated Frequency Limits	25 ... 400 hertz
Rated Frequency (f)	Supply Circuit 50 60 hertz
Package Width	101 millimetre
Package Length	115 millimetre
Package Height	61 millimetre
Invoice Description	A30-30-01 400-415V 50Hz / 415-440V 60Hz Contactor
Product Range	A Contactors

Enquire Now



Package Gross Weight	0.71 kilogram
Extended Product Type	A30-30-01 400-415V 50Hz / 415-440V 60Hz
Number of Aux Contacts NC	1
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 degree Celsius, Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +55 degree Celsius, Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 degree Celsius, Close to Contactor without T
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

[Download](#)

[Offers](#)

[Reviews](#)



Recently Viewed

 <p><u>A30-30-10 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL281001R8410 ₹2,242.94</p>	 <p><u>A30-30-10 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL281001R8610 ₹2,313.00</p>	 <p><u>A30-30-10 24V 50Hz / 24V 60Hz Contactor</u> 1SBL281001R8110 ₹2,453.22</p>	 <p><u>A40-30-01 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL321001R8401 ₹3,659.18</p>
---	---	--	---

Enquire Now

☐ Write to Us

1800 420 0707

@ contactabb.in@abb.com

(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

Facebook

Twitter

LinkedIn

Youtube

COMPANY

AboutUs

Sell Our With Sellers Us

BlogsExchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

PAYMENT METHODS

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

