

Genuine products

Dedicated  
Support

Doorstep Delivery

eMart[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > AL30-30-10 110V DC Contactor♥ [ADD TO WISH LIST](#)

Share with your friends



Automation &amp; Control

## AL30-30-10 110V DC Contactor

**₹4011.90** + ₹722.14 (GST 18%)

- 1 +

Buy Now

Add to Cart

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL283001R8610

[Be the first to review this product](#)Sold and delivered by **ANS ELECTRIC LLP**

AL30 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The AL... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: DC operated with solid core magnet circuit. The polarity on the coil terminals (A1+ and A2-) must be respected - Accessories: a wide range of accessories is available. AL... contactors are fitted with low consumption DC coils and are suitable for a direct control by PLC outputs.

Enquire Now



More about AL30-30-10 110V DC Contactor

Technical Specification	
MRP (Indian Rupees)	Not for Retail Sale
Compatibility	AL Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour, AC-3 1200 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-5-1, q = 40 °C 16 ampere, acc. to IEC 60947-4-1, Open Contactors q = 40 °C 65 ampere
Coil Consumption	Average Holding Value, from Warm State 3.5 watt, Average Pull-in Value, from Cold State 3.5 watt
Terminal Type	Screw Terminals
Rated Operational Voltage	Auxiliary Circuit 690 volt, Main Circuit 690 volt
Operate Time	Between Coil De-energization and NO Contact Opening 12 ... 18 millisecond, Between Coil Energization and NO Contact Closing 55 ... 110 millisecond
Rated Control Circuit Voltage (Uc)	DC Operation 110V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 9 KWT, (380 / 400 V) 15 KWT, (415 V) 15 KWT, (440 V) 18.5 KWT, (500 V) 18.5 KWT, (690 V) 15 KWT
Rated Operational Current DC-13 (Ie)	(125 V) 1.1 / 138 ampere, (24 V) 6 / 144 ampere, (250 V) 0.55 / 138 ampere, (48 V) 2.8 / 134 ampere, (72 V) 2 / 144 ampere
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 33 ampere, (380 / 400 V) 55 °C 32 ampere, (415 V) 55 °C 32 ampere, (440 V) 55 °C 32 ampere, (500 V) 55 °C 28 ampere, (690 V) 55 °C 18 ampere
Rated Operational Current AC-15 (Ie)	(220 / 240 V) 4 ampere, (24 / 127 V) 6 ampere, (380 / 440 V) 3 ampere, (500 V) 2 ampere, (690 V) 2 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 55 ampere, (690 V) 55 °C 55 ampere, (690 V) 70 °C 39 ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Frequency Limits	25 ... 400 hertz
Rated Frequency (f)	Supply Circuit 50 60 hertz
Number of Aux Contacts NO	1
Package Width	100 millimetre
Package Length	134 millimetre

Enquire Now

Package Height	62 millimetre
Invoice Description	AL30-30-10 110V DC Contactor
Product Range	AL Contactors
Package Gross Weight	0.85 kilogram
Extended Product Type	AL30-30-10 110V DC
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 degree Celsius, Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +55 degree Celsius, Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 degree Celsius, Close to Contactor without T
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

[Download](#)

[Offers](#)

[Reviews](#)

Enquire Now

Recently Viewed



**KL70-123C Light Element**

1SFA616070R1238

**Out of Stock**

☐ [Write to Us](#)

1800 420 0707

@ [contactabb.in@abb.com](mailto:contactabb.in@abb.com)

(Only for India Inquiries)

COMPANY

AboutSell Our BlogsExchange and Us With Sellers Returns Policy Us



INFORMATION

Privacy Terms How to create a Policy of Use Company Account

PAYMENT METHODS

FAQ

Bangalore, Karnataka, India.

 [Facebook](#)  [Twitter](#)

 [LinkedIn](#)  [Youtube](#)

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

Enquire Now

