



♥ [ADD TO WISH LIST](#)

Share with your friends



Automation & Control

Genuine products

Dedicated
Support

Doorstep Delivery

ABB A40-30-01 24V 50Hz / 24V 60Hz Contactor

₹3809.80 + ₹685.76 (GST 18%)

- 1 +

Buy Now

Add to Cart

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL321001R8101

[Be the first to review this product](#)

Sold and delivered by **PIGEON AGENCY**

A40 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Enquire Now

More about A40-30-01 24V 50Hz / 24V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)

Not for Retail Sale

Number of Main Contacts NO

3



Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour, AC-3 1200 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-5-1, q = 40 °C 16 ampere, acc. to IEC 60947-4-1, Open Contactors q = 40 °C 65 ampere
Coil Consumption	Average Holding Value 50 / 60 Hz 12.3 volt - ampere, Average Pull-in Value 50 Hz 125 volt - ampere, Average Pull-in Value 60 Hz 120 volt - ampere
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 14 millisecond, Between Coil De-energization and NO Contact Opening 4 ... 11 millisecond, Between Coil Energization and NC Contact Opening 6 ... 18 millisecond, Between Coil Energization and NO Con
Rated Control Circuit Voltage (Uc)	50 Hz 24V; 60 Hz 24V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-6b (Pe)	(230 / 240 V) 40 °C, 50 / 60 Hz 15 KVR, (230 / 240 V) 55 °C, 50 / 60 Hz 15 KVR, (230 / 240 V) 70 °C, 50 / 60 Hz 12 KVR, (400 / 415 V) 40 °C, 50 / 60 Hz 26 KVR, (400 / 415 V) 70 °C, 50 / 60 Hz 20 KVR, (400 / 415 V) 55 °C, 50 / 60 Hz 26 KVR, (440 V) 40 °C,
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 11 KWT, (380 / 400 V) 18.5 KWT, (415 V) 18.5 KWT, (440 V) 22 KWT, (500 V) 22 KWT, (690 V) 22 KWT
Rated Operational Current DC-13 (Ie)	(125 V) 1.1 / 138 ampere, (24 V) 6 / 144 ampere, (250 V) 0.55 / 138 ampere, (48 V) 2.8 / 134 ampere, (72 V) 2 / 144 ampere
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 40 ampere, (380 / 400 V) 55 °C 37 ampere, (415 V) 55 °C 37 ampere, (440 V) 55 °C 37 ampere, (500 V) 55 °C 33 ampere, (690 V) 55 °C 25 ampere
Rated Operational Current AC-15 (Ie)	(220 / 240 V) 4 ampere, (24 / 127 V) 6 ampere, (380 / 440 V) 3 ampere, (500 V) 2 ampere, (690 V) 2 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 60 ampere, (690 V) 55 °C 60 ampere, (690 V) 70 °C 42 ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x Ie AC-15
Rated Frequency Limits	25 ... 400 hertz
Rated Frequency (f)	Supply Circuit 50 60 hertz
Package Width	101 millimetre
Package Length	115 millimetre
Package Height	61 millimetre
Invoice Description	A40-30-01 24V 50Hz / 24V 60Hz Contactor
Product Range	A Contactors
Package Gross Weight	0.71 kilogram

Enquire Now



Extended Product Type	A40-30-01 24V 50Hz / 24V 60Hz
Number of Aux Contacts NC	1
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 degree Celsius, Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +55 degree Celsius, Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 degree Celsius, Close to Contactor without T
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

[Download](#)

[Offers](#)

[Reviews](#)



Recently Viewed

			
A40-30-01 400-415V 50Hz / 415-440V 60Hz Contactor	A40-30-10 110V 50Hz / 110-120V 60Hz Contactor	A40-30-10 400-415V 50Hz / 415-440V 60Hz Contactor	A50-30-00 110V 50Hz / 110-120V 60Hz Contactor
1SBL321001R8601	1SBL321001R8410	1SBL321001R8610	1SBL351001R8400
₹4,495.56	₹3,348.84	₹3,828.00	₹3,821.67

Enquire Now

<input type="checkbox"/> Write to Us	COMPANY	INFORMATION	PAYMENT METHODS
1800 420 0707	About Us	Sell Our BlogsExchange and Returns Policy	Privacy Policy
@ contactabb.in@abb.com	Us	With Sellers	Terms of Use
(Only for India Inquiries)		Us	How to create a Company Account
Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.			FAQ
Facebook			
Twitter			
LinkedIn			
Youtube			

