



♥ [ADD TO WISH LIST](#)

Share with your friends



Genuine products Dedicated Support Doorstep Delivery

Automation & Control  
**ABB**

eMart

## A40-30-01 400-415V 50Hz / 415-440V 60Hz Contactor

**₹3809.80** + ₹685.76 (GST 18%)

- 1 +

[Buy Now](#)

[Add to Cart](#)

Pin Code

[Calculate Shipping](#)

Please enter your PIN Code to check the best offers

Product Id#: 1SBL321001R8601

[Be the first to review this product](#)

Sold and delivered by **PIGEON AGENCY**

A40 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Enquire Now

### More about A40-30-01 400-415V 50Hz / 415-440V 60Hz Contactor

#### Technical Specification

MRP (Indian Rupees)

Not for Retail Sale

Number of Main Contacts NO

3



<b>Compatibility</b>	A Contactors
<b>Max Mechanical Switching Frequency</b>	3600 cycles per hour
<b>Max Electrical Switching Frequency</b>	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour, AC-3 1200 cycles per hour
<b>Conventional Free-air Thermal Current (Ith)</b>	acc. to IEC 60947-5-1, q = 40 °C 16 ampere, acc. to IEC 60947-4-1, Open Contactors q = 40 °C 65 ampere
<b>Coil Consumption</b>	Average Holding Value 50 / 60 Hz 12.3 volt - ampere, Average Pull-in Value 50 Hz 125 volt - ampere, Average Pull-in Value 60 Hz 120 volt - ampere
<b>Terminal Type</b>	Screw Terminals
<b>Rated Operational Voltage</b>	Main Circuit 690 volt
<b>Operate Time</b>	Between Coil De-energization and NC Contact Closing 7 ... 14 millisecond, Between Coil De-energization and NO Contact Opening 4 ... 11 millisecond, Between Coil Energization and NC Contact Opening 6 ... 18 millisecond, Between Coil Energization and NO Con
<b>Rated Control Circuit Voltage (Uc)</b>	50 Hz 400-415V; 60 Hz 415-440V
<b>Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1</b>	8 x Ie AC-3
<b>Rated Operational Power AC-6b (Pe)</b>	(230 / 240 V) 40 °C, 50 / 60 Hz 15 KVR, (230 / 240 V) 55 °C, 50 / 60 Hz 15 KVR, (230 / 240 V) 70 °C, 50 / 60 Hz 12 KVR, (400 / 415 V) 40 °C, 50 / 60 Hz 26 KVR, (400 / 415 V) 70 °C, 50 / 60 Hz 20 KVR, (400 / 415 V) 55 °C, 50 / 60 Hz 26 KVR, (440 V) 40 °C,
<b>Rated Operational Power AC-3 (Pe)</b>	(220 / 230 / 240 V) 11 KWT, (380 / 400 V) 18.5 KWT, (415 V) 18.5 KWT, (440 V) 22 KWT, (500 V) 22 KWT, (690 V) 22 KWT
<b>Rated Operational Current DC-13 (Ie)</b>	(125 V) 1.1 / 138 ampere, (24 V) 6 / 144 ampere, (250 V) 0.55 / 138 ampere, (48 V) 2.8 / 134 ampere, (72 V) 2 / 144 ampere
<b>Rated Operational Current AC-3 (Ie)</b>	(220 / 230 / 240 V) 55 °C 40 ampere, (380 / 400 V) 55 °C 37 ampere, (415 V) 55 °C 37 ampere, (440 V) 55 °C 37 ampere, (500 V) 55 °C 33 ampere, (690 V) 55 °C 25 ampere
<b>Rated Operational Current AC-15 (Ie)</b>	(220 / 240 V) 4 ampere, (24 / 127 V) 6 ampere, (380 / 440 V) 3 ampere, (500 V) 2 ampere, (690 V) 2 ampere
<b>Rated Operational Current AC-1 (Ie)</b>	(690 V) 40 °C 60 ampere, (690 V) 55 °C 60 ampere, (690 V) 70 °C 42 ampere
<b>Rated Making Capacity AC-3 acc. to IEC 60947-4-1</b>	10 x Ie AC-3
<b>Rated Breaking Capacity acc. to IEC 60947-5-1</b>	10 x Ie AC-15
<b>Rated Frequency Limits</b>	25 ... 400 hertz
<b>Rated Frequency (f)</b>	Supply Circuit 50 60 hertz
<b>Package Width</b>	101 millimetre
<b>Package Length</b>	115 millimetre
<b>Package Height</b>	61 millimetre
<b>Invoice Description</b>	A40-30-01 400-415V 50Hz / 415-440V 60Hz Contactor
<b>Product Range</b>	A Contactors
<b>Package Gross Weight</b>	0.71 kilogram

Enquire Now



Extended Product Type	A40-30-01 400-415V 50Hz / 415-440V 60Hz
Number of Aux Contacts NC	1
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 degree Celsius, Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +55 degree Celsius, Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 degree Celsius, Close to Contactor without T
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

- Download

▼
- Offers

▼
- Reviews

▼

Recently Viewed

 <p><u>A40-30-10 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL321001R8410 ₹3,348.84</p>	 <p><u>A40-30-10 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL321001R8610 ₹3,828.00</p>	 <p><u>A50-30-00 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL351001R8400 ₹3,821.67</p>	 <p><u>A63-30-00 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL371001R8400 ₹6,343.00</p>
---	---	--	---

Enquire Now

☐ Write to Us

1800 420 0707

@ [contactabb.in@abb.com](mailto:contactabb.in@abb.com)

(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

Facebook

Twitter

LinkedIn

Youtube

COMPANY

AboutUs

Sell Our Us

With Sellers

BlogsExchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

PAYMENT METHODS

