

[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > A75-30-00 24V 50Hz / 2



Share with your friends



Genuine products

Dedicated
Support

Doorstep Delivery



Automation & Control

eMart

A75-30-00 24V 50Hz / 24V 60Hz Contactor

Out of stock

Upon Request

Product Id#: 1SBL411001R8100

[Be the first to review this product](#)

A75 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC / 1000 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Enquire Now



More about A75-30-00 24V 50Hz / 24V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	3
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 150 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40
Coil Consumption	Average Holding Value 50 / 60 Hz 18 5.5 volt - Value 50 Hz 190 volt - ampere, Average Pull-in ampere
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 1000 volt
Operate Time	Between Coil De-energization and NO Contact millisecond, Between Coil Energization and NO millisecond
Rated Control Circuit Voltage (Uc)	50 Hz 24V; 60 Hz 24V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-6b (Pe)	(230 / 240 V) 40 °C, 50 / 60 Hz 28 KVR, (230 / 28 KVR, (230 / 240 V) 70 °C, 50 / 60 Hz 24.5 KVR, 50 / 60 Hz 48 KVR, (400 / 415 V) 70 °C, 50 / 60 55 °C, 50 / 60 Hz 48 KVR, (440 V) 40 °C
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 22 KWT, (380 / 400 V) 37 K V) 40 KWT, (500 V) 45 KWT, (690 V) 40 KWT
Rated Operational Current AC-3 (Ie)	(1000 V) 55 °C 28 ampere, (220 / 230 / 240 V) 400 V) 55 °C 75 ampere, (415 V) 55 °C 75 ampere, (500 V) 55 °C 65 ampere, (690 V) 55 °C

Enquire Now

Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 125 ampere, (690 V) 55 °C 105 ar ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Frequency Limits	25 ... 400 hertz
Package Width	140 millimetre
Package Length	146 millimetre
Package Height	96 millimetre
Invoice Description	A75-30-00 24V 50Hz / 24V 60Hz Contactor
Product Range	A Contactors
Package Gross Weight	1.16 kilogram
Extended Product Type	A75-30-00 24V 50Hz / 24V 60Hz
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 deg Contactor without Thermal O/L Relay (0.85 ... Celsius, Close to Contactor Fitted with Therm degree Celsius, Close to Contactor without T
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	France (FR) - Imported by ABB India Limited

[Download](#)

[Reviews](#)

Recently Viewed



 <p><u>A75-30-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL411001R8600 Out of Stock</p>	 <p><u>A9-40-00 24V 50Hz / 24V 60Hz Contactor</u> 1SBL141201R8100 Out of Stock</p>	 <p><u>A9-22-00 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL141501R8400 ₹853.42</p>	<u>A9-</u>
---	--	--	------------


☐ Write to Us


1800 420 0707


@ contactabb.in@abb.com


(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

 [Facebook](#)

 [Twitter](#)

 [Linkedin](#)

 [Youtube](#)

COMPANY

INFORMATION

About Us

Sell Our Us

BlogsWith Sellers

Exchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

Enquire Now

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bang

https://shop.in.abb.com/1sbl411001r8100/a75-30-00-24v-50hz-24v-60hz-contactor.html?srsId=AfmBOopszxiyUwLBkXRITAQWHYAFb1iMJ8leJdbxuc...

4/4