MLBL-07Y 1/4



PRODUCT-DETAILS

MLBL-07Y MLBL-07Y LED block



General Information	
Extended Product Type	MLBL-07Y
Product ID	1SFA611621R1073
EAN	7320500544884
Catalog Description	MLBL-07Y LED block
Long Description	The MLBL-07Y LED block is: - Yellow - Illuminated - Front mounting - 230 V This LED block is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	85369001

MLBL-07Y 2/4

Popular Downloads	
Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M020
Dimensions	
Product Net Width	0.01 m
Product Net Height	0.044 m
Product Net Depth /	0.042 m
Length	0.041
Product Net Weight	0.01 kg
Technical	
Ambient Air Temperature	Operation -25 +70 °C Storage -40 +85 °C
Color	Yellow
Illumination	Illuminated
Lamp Type	230 V AC, integrated LED
Mounting Type	Front mounting
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	230 V AC
	Flexible with Ferrule 2 x 0.752.5 mm ² Flexible with Insulated Ferrule 1 x 0.752.5 mm ² Flexible with Insulated Ferrule 2 x 0.752.5 mm ² Flexible 1 x 0.75 2.5 mm ² Flexible 2 x 0.75 2.5 mm ² Solid 1 x 0.752.5 mm ²
Connection Type	Solid 2 x 0.752.5 mm ²
Connection Type Terminal Type	Screw Clamp Screw Terminals
Tightening Torque	0.9 N·m
Wire Stripping Length	8 mm
Suitable For	MCBH-00
	MCBH5-00 MPI MP2 MP3
	MPMT3 MPMT3 MPMP3
	M2SS: M2SS: M2SS:
	M2552 M2555 M2555 M2556
	M35S3 M35S3 M35S3 M35S3
	M3554 M3555 M3555
	M3SS7 M3SS8 M9M1
Suitable for Product	Pilot Devices

MLBL-07Y 3/4

Class

Technical UL/CSA	
Connecting Capacity	1x 1814 AWG
UL/CSA	2x 1814 AWG

Environmental Degree of Protection Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	SEMKO_SE-56219
CQC Certificate	CQC2008010305274953
cULus Certificate	9AKK107046A9925
Declaration of Conformity - CCC	2020980305001106
Declaration of Conformity - CE	2CMT2015-005452
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	E-14107
EAC Certificate	1SFC150017D1101

Container Information	
Package Level 1 Units	bag 10 piece
Package Level 1 Width	0.135 m
Package Level 1 Depth / Length	0.155 m
Package Level 1 Height	0.025 m
Package Level 1 Gross Weight	0.11 kg
Package Level 1 EAN	7320500373057

Classifications	
Object Classification	E
Code	

MLBL-07Y 4/4

ETIM 6	EC000204 - Lamp holder block for control circuit devices
ETIM 7	EC000204 - Lamp holder block for control circuit devices
ETIM 8	EC000204 - Lamp holder block for control circuit devices
eClass	V11.0 : 27371209
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	2315777
E-Number (Norway)	4373115
E-Number (Sweden)	3705069

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Control\ Products\ \rightarrow\ Pilot\ Devices\ \rightarrow\ Accessories$ $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Control\ Products\ \rightarrow\ Pilot\ Devices\ \rightarrow\ Modular\ Plastic\ Range$ $Medium\ Voltage\ Products\ and\ Systems\ \rightarrow\ Service\ \rightarrow\ Spares\ and\ Consumables\ \rightarrow\ Parts\ \rightarrow\ All\ Spare\ Parts\ (Relays-SWG-CB)$







