

PRODUCT-DETAILS

AX150-30-11-84

AX150-30-11-84 Contactor



General Information	
Extended Product Type	AX150-30-11-84
Product ID	1SFL991074R8411
EAN	7320500500170
Catalog Description	AX150-30-11-84 Contactor
Long Description	AX150-30-11-84 Contactor

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Instructions and Manuals	9AKK107492A7060
CAD Dimensional Drawing	2CDC001079B0201

Dimensions	
------------	--

Product Net Width	102 mm
Product Net Depth / Length	123.5 mm
Product Net Height	148 mm
Product Net Weight	1.9 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40^\circ\text{C}$ 190 A
Rated Operational Current AC-1 (I_e)	(690 V) 40°C 190 A (690 V) 55°C 145 A (690 V) 70°C 130 A
Rated Operational Current AC-3 (I_e)	(415 V) 55°C 150 A (440 V) 55°C 100 A (500 V) 55°C 100 A (690 V) 55°C 82 A (380 / 400 V) 55°C 150 A (220 / 230 / 240 V) 55°C 150 A
Rated Operational Power AC-3 (P_e)	(415 V) 75 kW (440 V) 59 kW (500 V) 59 kW (690 V) 75 kW (380 / 400 V) 75 kW (220 / 230 / 240 V) 45 kW
Rated Breaking Capacity AC-3	8 x I_e AC-3
Rated Making Capacity AC-3	10 x I_e AC-3
Rated Short-time Withstand Current Low Voltage (I_{cw})	at 40°C Ambient Temp, in Free Air, from a Cold State 10 s 800 A at 40°C Ambient Temp, in Free Air, from a Cold State 15 min 160 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 min 350 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 s 1320 A at 40°C Ambient Temp, in Free Air, from a Cold State 30 s 500 A
Maximum Electrical Switching Frequency	300 cycles per hour
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) U_c (at $\Theta \leq 70^\circ\text{C}$)
Rated Control Circuit Voltage (U_c)	50 Hz 110 V 60 Hz 110 ... 120 V
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40
Terminal Type	Main Circuit: Bars

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 55 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CQC Certificate	CQC2013010304646592
Declaration of Conformity - CCC	2020980304001063
Declaration of Conformity - CE	2CMT2015-005443
UL Certificate	20160916- E36588

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	140 mm
Package Level 1 Depth / Length	170 mm
Package Level 1 Height	130 mm
Package Level 1 Gross Weight	2.1 kg
Package Level 1 EAN	7320500500170

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AX Contactors → AX150

