

[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > A9-30-01 400-415V 50Hz / 415-



♥ **ADD TO WISH LIST**

Share with your friends



Genuine products

Dedicated
Support

Doorstep Delivery



eMart

Automation & Control

A9-30-01 400-415V 50Hz / 415-440V 60Hz Contactor

₹700.90 + ₹126.16 (GST 18%)

- 1 +

Buy Now

Add to Cart

More Offers available from 2 sellers starting at
INR. 827.06

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL141001R8601

Be the first to review this product

Enquire Now



Sold and delivered by **PIGEON AGENCY**

A 9 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

More about A9-30-01 400-415V 50Hz / 415-440V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	3
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-5-1, q = 40 °C 16 ampere, acc Contactors q = 40 °C 26 ampere
Coil Consumption	Average Holding Value 50 / 60 Hz 8 2 volt - am Value 50 Hz 74 volt - ampere, Average Pull-in V ampere
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NC Contact millisecond, Between Coil De-energization and ... 11 millisecond, Between Coil Energization ar ... 21 millisecond, Between Coil Energization ar
Rated Control Circuit Voltage (Uc)	50 Hz 400-415V; 60 Hz 415-440V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3

Enquire Now



Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 2.2 KWT, (380 / 400 V) 4 KWT, (500 V) 5.5 KWT, (690 V) 5.5 KWT
Rated Operational Current DC-13 (Ie)	(125 V) 1.1 / 138 ampere, (24 V) 6 / 144 ampere, (48 V) 2.8 / 134 ampere, (72 V) 2 / 144 ampere
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 9 ampere, (380 / 400 V) 55 °C 9 ampere, (440 V) 55 °C 9 ampere, (500 V) 55 °C 7 ampere, (690 V) 55 °C 7 ampere
Rated Operational Current AC-15 (Ie)	(220 / 240 V) 4 ampere, (24 / 127 V) 6 ampere, (500 V) 2 ampere, (690 V) 2 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 25 ampere, (690 V) 55 °C 22 ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x Ie AC-15
Rated Frequency Limits	25 ... 400 hertz
Rated Frequency (f)	Supply Circuit 50 60 hertz
Package Width	78 millimetre
Package Length	76 millimetre
Package Height	47 millimetre
Invoice Description	A9-30-01 400-415V 50Hz / 415-440V 60Hz Contactor
Product Range	A Contactors
Package Gross Weight	0.34 kilogram
Extended Product Type	A9-30-01 400-415V 50Hz / 415-440V 60Hz Contactor
Number of Aux Contacts NC	1
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 degrees Celsius, Close to Contactor without Thermal O/L Relay (0.85 ... 1.05 degrees Celsius), Close to Contactor Fitted with Thermal Relay (0.85 ... 1.05 degrees Celsius), Close to Contactor without Thermal Relay (0.85 ... 1.05 degrees Celsius)
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 1000 volt

Enquire Now



Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

[Download](#)

[Offers](#)

[Reviews](#)

Recently Viewed

 <p><u>A9-30-10 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL141001R8410 ₹673.19</p>	 <p><u>A9-30-10 24V 50Hz / 24V 60Hz Contactor</u> 1SBL141001R8110 ₹673.19</p>	 <p><u>A12-30-01 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL161001R8401 ₹755.79</p>	<div>Enquire Now</div>
---	---	--	------------------------

☐ Write to Us

1800 420 0707

@ contactabb.in@abb.com

(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya
Industrial Area IV, Peenya 560058,
Bangalore, Karnataka, India.

Facebook

Twitter

LinkedIn

Youtube

COMPANY

Information

About Us

Sell Our Us

Our With Sellers

Blogs

Exchange and Returns

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

Enquire Now

