



PRODUCT-DETAILS

**SB201-C63DC**  
Miniature Circuit Breaker - SB200 DC - 1P - 63  
A - C



General Information	
Extended Product Type	SB201-C63DC
Product ID	1SYS251067R0634
Catalog Description	Miniature Circuit Breaker - SB200 DC - 1P - 63 A - C
Long Description	System pro M compact SB200 DC Miniature Circuit Breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in C-characteristics, different configurations (1P, 2P), breaking capacities (up to 6 kA at 240/415 V AC) and rated currents (up to 63A). All MCBs of the product range SB200 DC comply with IS/IEC 60947-2, allowing the use for residential, commercial and industrial applications.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 91.69 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
Sustainable Material Content in Packaging	FSC 100% Paper - 43.11 % FSC 100% Paper - 30.23 %

(wt. %)	FSC Mix Paper - 23.68 % 0 % 0 %
Extended Product Lifetime	Product Durability
End Of Life Disassembling Instructions	1SYM100001D1196
Environmental Product Declaration - EPD	9AKK108469A9162

Technical

Rated Operational Current (I <sub>e</sub> )	63 A
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	6000 kA
Power Supply Connection	Please Note Polarity of Device
Electrical Endurance	1000DC cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	1
Number of Poles	1P
Tightening Torque	2 N·m
Actuator Type	Toggle
Actuator Marking	I / O
Actuator Material	Insulation Group II, Black, Sealable
Recommended Screw Driver	Pozidriv 2
Remarks	IP40 in enclosure with cover
Connecting Capacity	rigid: 25 mm <sup>2</sup> ; flexible: 16 mm <sup>2</sup>

Electrical

Tripping Characteristic	C
Rated Voltage (U <sub>r</sub> )	250 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Rated Current (I <sub>n</sub> )	63 A
Rated Short-Circuit Capacity	6 kA

Design

Housing Material	Insulation Group I, RAL 7035
------------------	------------------------------

Material Compliance

RoHS Information	1SYM100001D1018
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	43546

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	Product Not in WEEE Scope

<b>Environmental</b>	
Ambient Air Temperature	Operation -25 ... +55 °C
Reference Ambient Air Temperature	55 °C
Degree of Protection	IP20
Environmental Conditions	28 cycle 55°C @ 90-96% 25°C @ 95-100%
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g / 2 shock / 13 ms

<b>Dimensions</b>	
Product Net Width	17.5 mm
Product Net Height	85 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.125 kg
Built-In Depth (t <sub>2</sub> )	69 mm

<b>Ordering</b>	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.125 kg

<b>Certificates and Declarations</b>	
Declaration of Conformity - CE	9AKK107492A3487

<b>Installation</b>	
Instructions and Manuals	No document needed
Mounting Position	Any

<b>Popular Downloads</b>	
Data Sheet, Technical Information	No document needed

<b>External Classifications and Standards</b>	
ETIM 9	EC000042 - Miniature circuit breaker (MCB)

eClass	V11.0 : 27141901
Object Classification	F
Code	
Standards	IS/IEC 60947-2

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs → SB200 DC

