



LV HRC fuse element, NH00, In: 63 A, gG, Un AC: 690 V, Un DC: 250 V, Combined indicator, live grip lugs

Model		
product designation	LV HRC fuse link	
design of the product	With blade contacts	
design of an identification indicator	Combination alarms	
General technical data		
size of fuse system according to EN 60269-1	NH00	
operating class of the fuse link	gG	
mounting type	non-insulated grip lugs	
type of voltage of the operating voltage	AC/DC	
supply voltage		
• at AC	690 V	
• at DC	250 V	
Mechanical Design		
net weight	620 g	
Certificates		
reference code according to IEC 81346-2	FC	
Approvals Certificates		
General Product Approval	Marine / Shipping	other

[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

[Miscellaneous](#)

Environment

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA7822-6RC>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3NA7822-6RC>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA7822-6RC

last modified:

6/5/2023 

