



Acti 9 - fuse-disconnector STI - 1 pole - 25 A - for fuse 10.3 x 38 mm

A9N15636

١	/I	a	ı	r	1

Range	Acti9
Product name	Acti9 STI
Product or component type	Fuse-disconnector
Device short name	STI
Poles description	1P

Complementary		
[In] rated current	2 A 4 A 6 A 10 A 16 A 20 A 25 A	
Fuse curve	AM GG	
Fuse size	10.3 x 38 mm	
[Ue] rated operational voltage	500 V AC	
[Ui] rated insulation voltage	500 V AC 50/60 Hz	
Mounting mode	Clip-on	
Mounting support	DIN rail	
9 mm pitches	2	
Height	81 mm	
Width	18 mm	
Depth	75 mm	
Colour	White	
Connections - terminals	Screw clamp terminals1 cable(s) 0.7510 mm² rigid Screw clamp terminals1 cable(s) 0.56 mm² flexible Screw clamp terminals2 cable(s) 0.754 mm² rigid Screw clamp terminals2 cable(s) 0.56 mm² flexible	
Wire stripping length	12 mm	

Environment

Tightening torque

Standards IEC 60269-1/2

2 N.m

	IEC EN 60947-3
IP degree of protection	IP20
Pollution degree	3
Ambient air temperature for operation	-2060 °C
Ambient air temperature for storage	-4080 °C
Packing Units	
Unit Type of Package 1	PCE

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.8 cm
Package 1 Width	1.8 cm
Package 1 Length	8.4 cm
Package 1 Weight	54.5 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.6 cm
Package 2 Width	9.4 cm
Package 2 Length	22.2 cm
Package 2 Weight	710 g
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	9.05 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty 12 months

Recommended replacement(s)