



MATERIAL FACT SHEET

236719 AJ65VBTCU-68ADIN

General Data

Product Hierarchy	IAD50501
	Modular PLC
	A2C-PLC
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000236719

FA-MOD PLC: Analogue I/O Module

Series	CC-LINK
Type	REMOTE ANALOG INPUT
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Analogue Inputs	8
Input Current Range (mA)	0-20; 4-20
Wiring	CONNECTOR
Int. Current Consumption (A)	0,1

Product Dimensions & Weight

Width (mm)	41
Height (mm)	115
Depth (mm)	67
Weight (kg)	0,17

Logistic Dimensions & Gross Weight

Length (cm)	17,0
Width (cm)	8,0
Height (cm)	6,6
Gross Weight (kg)	0,232
Volume (cdm)	0,898

Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

Life Cycle

Sales Start	09.12.2010
Predecessor	No Predecessor

Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	68-12-2
REACH Substance CAS Number (2)	7439-92-1
REACH Substance CAS Number (3)	80-05-7

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=AJ65VBTCU-68ADIN&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=AJ65VBTCU-68ADIN&doc-lang=en

Product Packaging

Cardboard (g)	0
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
168345	A6CON-P514 One-touch connector plug for CC-Link remote I/O modules (20 pcs) Class 100100215: FA-MOD PLC: Other Option
168346	A6CON-P520 One-touch connector plug for CC-Link remote I/O modules (20 pcs) Class 100100215: FA-MOD PLC: Other Option
168347	A6CON-L5P 5-pin connector for CC-Link remote I/O, 10 pieces Class 100100215: FA-MOD PLC: Other Option
168348	A6CON-PW5P Connector for CC-Link Remote I/O; Resistance 110 Ohm; Set (10 pcs) Class 100100215: FA-MOD PLC: Other Option
280085	A6CON-LJ5P CC-link communication for online connector (5 pcs) Class 100100215: FA-MOD PLC: Other Option
280088	A6CON-PW5P-SOD Power FG for one-touch connector plug; (10 pcs) Class 100100215: FA-MOD PLC: Other Option