



## MATERIAL FACT SHEET

### 236718 AJ65VBTCU-68DAVN

#### General Data

Product Hierarchy	IAD50501
	Modular PLC
	A2C-PLC
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000236718](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000236718)

#### FA-MOD PLC: Analogue I/O Module

Series	CC-LINK
Type	REMOTE ANALOG OUTPUT
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Analogue Outputs	8
Output Voltage Range (V)	-10-10; 0-5; 1-5
Wiring	CONNECTOR
Int. Current Consumption (A)	0,15

#### Product Dimensions & Weight

Width (mm)	41
Height (mm)	115
Depth (mm)	67
Weight (kg)	0,16

#### Logistic Dimensions & Gross Weight

Length (cm)	17,0
Width (cm)	8,0
Height (cm)	6,6
Gross Weight (kg)	0,227
Volume (cdm)	0,898

#### Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

#### Life Cycle

Sales Start	09.12.2010
Predecessor	No Predecessor

#### Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	<a href="#">68-12-2</a>
REACH Substance CAS Number (2)	<a href="#">7439-92-1</a>
REACH Substance CAS Number (3)	<a href="#">80-05-7</a>

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65VBTCU-68DAVN&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65VBTCU-68DAVN&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65VBTCU-68DAVN&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65VBTCU-68DAVN&amp;doc-lang=en</a>
Network configuration file URL	X

### Product Packaging

Cardboard (g)	0
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3
Wood (g)	0
Glass (g)	0
Others (g)	0

### Compatible products

Material	Description / Price List Text / Classification
168345	A6CON-P514 One-touch connector plug for CC-Link remote I/O modules (20 pcs) Class 100100215: FA-MOD PLC: Other Option
<a href="#">168346</a>	A6CON-P520 One-touch connector plug for CC-Link remote I/O modules (20 pcs) Class 100100215: FA-MOD PLC: Other Option
<a href="#">168347</a>	A6CON-L5P 5-pin connector for CC-Link remote I/O, 10 pieces Class 100100215: FA-MOD PLC: Other Option
<a href="#">168348</a>	A6CON-PW5P Connector for CC-Link Remote I/O; Resistance 110 Ohm; Set (10 pcs) Class 100100215: FA-MOD PLC: Other Option
280085	A6CON-LJ5P CC-link communication for online connector (5 pcs) Class 100100215: FA-MOD PLC: Other Option
<a href="#">280088</a>	A6CON-PW5P-SOD Power FG for one-touch connector plug; (10 pcs) Class 100100215: FA-MOD PLC: Other Option