

Specifications



Photo is representative



Eaton BAB3080HS

Eaton BAB thermal magnetic circuit breaker, Quicklag industrial thermal-magnetic circuit breaker, 80 A, 10 kAIC, Three-pole, 240 V, Non-Interchangeable, Q32, BAB, 24/48 Vdc Shunt trip

General specifications

PRODUCT NAME	Eaton BAB thermal magnetic circuit breaker
CATALOG NUMBER	BAB3080HS
UPC	786679509708
PRODUCT LENGTH/DEPTH	4.1 in
PRODUCT HEIGHT	3.5 in
PRODUCT WIDTH	3.6 in
PRODUCT WEIGHT	1.29 lb
WARRANTY	1 year
CERTIFICATIONS	UL Listed CSA Certified
CATALOG NOTES	HACR rated

Physical Attributes	
CIRCUIT BREAKER TYPE	BAB
MOUNTING METHOD	Bolt-on
NUMBER OF POLES	Three-pole
TYPE	Quicklag industrial thermal-magnetic circuit breaker

Performance Ratings	
AMPERAGE RATING	80 A
INTERRUPT RATING	10 kAIC
TRIP TYPE	Non-Interchangeable
VOLTAGE RATING	240 V - 240 V

Miscellaneous	
QUANTITY	32
SPECIAL FEATURES	Bolt-on mounting

Resources	
MULTIMEDIA	Circuit Breakers Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BAB3080HS

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. Follow us on social media to get the latest product and support information.
All other trademarks are property of their respective owners.

