



Acti 9 - MINs - silent electronic timer - adjustable from 0.5 to 20 minutes

CCT15232

Main

Range of product	Acti9
Product name	Acti9 MIN
Device short name	MINs
Product or component type	Silent electronic timer
Product compatibility	Mechanical compatibility with electrical comb busbars
Colour tint	White (RAL 9003)

Complementary

Device application	Building
Load type	230 V AC halogen lamp 2300 W 230 V AC incandescent lamp 2300 W Fluorescent lamp 9 x electronic ballast 7 W Dual mounted fluorescent tubeconventional ballast 2300 VA Fluorescent tubeelectronic ballast 300 VA Non-corrected fluorescent tubeconventional ballast 2300 VA Serial-corrected fluorescent tubeconventional ballast 2300 VA Fluorescent lamp 7 x electronic ballast 11 W Fluorescent lamp 7 x electronic ballast 15 W Fluorescent lamp 7 x electronic ballast 20 W Fluorescent lamp 7 x electronic ballast 23 W Fluorescent lamp 7 x electronic ballast 1500 VA Parallel-corrected fluorescent tubeconventional ballast 400 VA
Power consumption in VA	6 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Time delay	Adjustable from 0.5 to 20 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals - <= 6 mm²
Electrical insulation class	Class II
Width	18 mm
Height	89 mm
Depth	66 mm
Product weight	75 g

Environment

Ambient air temperature for operation	-1050 °C
IP degree of protection	IP20 B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	7.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	93.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	130
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	12.636 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty 18 months

Recommended replacement(s)