Product data sheet

Specifications

Tandem circuit breaker, Homeline Canadian, 2 x 1 pole at 15A, 120/240VAC, 10kA AIR, plug in, UL

CHOMT1515

Main

Range of product	Homeline
Product or component type	Miniature circuit-breaker
[In] rated current	15 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Plug-on
Poles description	1P
Short-circuit current	10 kA
Circuit breaker type	Tandem
Circuit breaker application	HACR rated
Electrical connection	Screw clamp terminals

Complementary

Number of spaces required	1
AWG gauge	AWG 14...AWG 8 aluminum/copper

Environment

Product certifications	CSA
Ambient air temperature for operation	104 °F (40 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.00 in (2.540 cm)
Package 1 Width	3.10 in (7.874 cm)
Package 1 Length	3.30 in (8.382 cm)
Package 1 Weight	6.880 oz (195.045 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.40 in (8.636 cm)
Package 2 Width	3.80 in (9.652 cm)
Package 2 Length	10.20 in (25.908 cm)
Package 2 Weight	4.519 lb(US) (2.050 kg)

Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	10.90 in (27.686 cm)
Package 3 Width	7.80 in (19.812 cm)
Package 3 Length	17.30 in (43.942 cm)
Package 3 Weight	45.801 lb(US) (20.775 kg)

Life Is On | **Schneider**
Electric

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	**23**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
China RoHS Regulation	**China RoHS declaration**

Use Again

Repack and remanufacture

Take-back	**No**