

- Home
- Products
- Download
- Resource
- Support
- Sales Locations

Panasonic Industry > Automation Controls Top > FA Sensors & Components > Pressure Sensors / Flow Sensors > Pressure Sensors / Flow Sensors > DP-102

Pressure Sensors / Flow Sensors

Pressure Sensors / Flow Sensors >

Dual Display Digital Pressure Sensor [For Gas] DP-100 >

DP-102

Pressure Digital Display >

Pressure Head-separated >

Discontinued Products >

DP-102 | Dual Display Digital Pressure Sensor [For Gas] DP-100

Download

Catalog/
Datasheet

CAD

Manual



*Photo may vary from actual product.



Contact Us

**Technical Inquiries,
Purchase Support &
Additional Assistance**

Technical inquiry

Business inquiry



Other inquiry

Product Number	DP-102
Number	DP-102
Product	Dual Display Digital Pressure Sensor [For Gas]
Details	Standard pressure port type
Product Name	Dual Display Digital Pressure Sensor [For Gas] DP-102

Contact Us

Technical inquiry

Business inquiry

Other inquiry

Spec Detail



Combination Products (Options)



As of April 26, 2025 (JST)

*Specifications and design of the products are subject to change without notice for the product improvement.

Spec Detail

Specifications and design of the products are subject to change without notice for the product improvement.

Item	Specifications
Product Number	DP-102
Part Number	DP-102
Products Name	Dual Display Digital Pressure Sensor [For Gas] 



Item	Specifications
Product details	Standard pressure port type
Regulatory compliance and certification	CE Marking (EMC Directive, RoHS Directive), UKCA Marking (EMC Regulations, RoHS Regulations)
Type of pressure	Gauge pressure
Rated pressure range	-0.100 to +1.000 MPa
Set pressure range	-0.101 to +1.010 MPa -101 to +1,010 kPa -1.03 to +10.30 kgf/cm ² -1.01 to +10.10 bar -14.6 to +146.4 psi
Pressure withstandability	1.5 MPa
Applicable fluid	Non-corrosive gas
Supply voltage	12 to 24 V DC \pm 10 % Ripple P-P 10 % or less
Power consumption	Normal operation : 720 mW or less (Current consumption 30 mA or less at 24 V supply voltage) ECO mode : 480 mW or less at STD (Current consumption 20 mA or less at 24 V supply voltage) 360 mW or less at FULL (Current consumption



Item	Specifications
	mA or less at 24 V supply voltage)
Comparative output	<p><NPN output> NPN open-collector transistor</p> <ul style="list-style-type: none"> - Maximum sink current : 100 mA - Applied voltage : 30 V DC or less (between comparative output and 0 V) - Residual voltage : 2 V or less (at 100 mA sink current)
Comparative output : Output operation	NO / NC (selectable by key operation)
Comparative output : Output modes	EASY mode / Hysteresis mode / Window comparator mode
Comparative output : Hysteresis	Minimum 1 digit (variable)(however, 2 digits when using psi unit)
Comparative output : Repeatability	±0.2 % F.S. (within ±2 digits)
Comparative output : Response time	2.5 ms, 5 ms, 10 ms, 25 ms, 50 ms, 100 ms, 250 ms, 500 ms, 1,000 ms, 5,000 ms, selectable by key operation
Comparative output : Short-circuit protection	Incorporated
External input	-



Item	Specifications
Analog voltage output	-
Analog current output	-
Display	4 digits + 4 digits 3-color LCD display (Display refresh rate : 250 ms, 500 ms, 1,000 ms, selectable by key operation)
Display : Displayable pressure range	-0.101 to +1.010 MPa -101 to +1,010 kPa -1.03 to +10.30 kgf/cm ² -1.01 to +10.10 bar -14.6 to +146.4 psi
Indicator	Orange LED (Comparative output 1 operation indicator, comparative output 2 operation indicator : Lights up when each comparative output is ON)
Protection	IP40 (IEC)
Ambient temperature	-10 to +50 °C +14 to +122 °F , Storage : -10 to +60 °C +14 to +140 °F
Ambient humidity	35 to 85 % RH (No dew condensation or icing allowed), Storage : 35 to 85 % RH
Voltage withstandability	1,000 V AC for min. between supply terminals 

Item	Specifications
	connected together and enclosure
Insulation resistance	50M Ω or more with 500 V DC megger between all supply terminals connected together and enclosure
Vibration resistance	10 to 500 Hz frequency, 3 mm 0.118 in double amplitude or maximum acceleration 196 m/s ² , in X, Y and Z directions for two hours each (when panel is mounted: 10 to 150 Hz frequency, 0.75 mm 0.030 in double amplitude or maximum acceleration 49 m/s ² , in X, Y and Z directions for two hours each)
Shock resistance	100 m/s ² acceleration (10 G approx.) in X, Y and Z directions three times each
Temperature characteristics	Within ± 1 % F.S. (at +20 °C +68 °F)
Pressure port	M5 female thread + R (PT) 1/8 male thread



Item	Specifications
Material	Enclosure : PBT (glass fiber reinforced), LCD display : Acrylic, Pressure port : Stainless steel (SUS303), Mounting threaded part : Brass (nickel plated), Switch part : Silicone rubber
Connecting method	Connector
Cable length	Total length up to 100 m 328.084 ft (less than 30 m 98.425 ft when conforming to CE marking) is possible with 0.3 mm ² , or more, cable
Weight	Net weight: 40 g approx., Gross weight: 130 g approx.
Accessories	CN-14A-C2 (Connector attached cable 2 m 6.562 ft): 1pc. (excluding M8 plug-in connector type)

Combination Products (Options)



	Model Number	Product Number	Product
No image	CN-14A	CN-14A	-
No image	CN-14A-C1	CN-14A-C1	-
No image	CN-14A-C2	CN-14A-C2	-
No image	CN-14A-C3	CN-14A-C3	-

[View More](#)

Recently checked products

Recently checked product numbers

- DP-101A-E-P | Dual Display Digital Pressure Sensor [For Gas] DP-100 >
- DP-101A | Dual Display Digital Pressure Sensor [For Gas] DP-100 >
- DP-101-E-P | Dual Display Digital Pressure Sensor [For Gas] DP-100 >
- DP-101 | Dual Display Digital Pressure Sensor [For Gas] DP-100 >
- CX-491-P | Compact Photoelectric Sensor CX-400 Ver.2 >



Contact Us

Control Components & Electronic Device Products Technical Support

Relays, Couplers, Connectors, Switches, and Other Control Components & Electronic Device Products

Contact Us

FA Sensors & Components, Motors Technical Support

FA Sensors, PLC ,Eco Power Meters, Times, Counters, Limit Switches and Other FA Sensors & Components

Contact Us

Motors Technical Support

Motors for FA & Industrial Application, Motors for Appliance & Automotive

Contact Us

Guidelines for Ordering and Usage

Requests to customers (FA Sensors & Components [Excluding motors])

Requests to customers (Dedicated to industrial motors)

Components & Devices



ys / Couplers

FA Sensors & Components

Fiber Sensors

Sensor Options

Static Control Devices

Motors for FA & Industrial Application



Connectors	Photoelectric	Wire-Saving	Laser Markers /	AC Servo
Switches	Sensors / Laser	Systems	2D Code	Motors for HVAC &
Encoders /	Sensors	Programmable	Readers	Automotive
Potentiometers	Micro	Controllers /	Machine Vision	
Transparent	Photoelectric	Motion	System	
Conductive Film	Sensors	Controller	Energy	
Cooling Fan	Light Curtains /	Human	Management	
	Safety	Machine	Solutions	
	Components	Interface		
	Area Sensors	Pressure		
	Inductive	Sensors / Flow		
	Proximity	Sensors		
	Sensors	Measurement		
	Particular Use	Sensors		
	Sensors			

[Site Map](#) | [Terms of Use](#) | [Privacy Policy](#) | [Cookie Policy](#) | [Panasonic Holdings Corporation](#)

[Panasonic Industry Sales Asia Pacific](#) Copyright © Panasonic Industry Co., Ltd.

 [Area/Country](#)

