



## MATERIAL FACT SHEET

### 165271 FX3U-4DA-ADP

#### General Data

Product Hierarchy	IAD213
	Compact PLC
	FX3U
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000165271](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000165271)

#### FA-COM PLC: Analogue I/O Module

Series	MELSEC-F SERIES
Type	FX3U
Power Supply (V)	24
Current Type	DC
Integrated Analogue Outputs	4
Output Voltage Range (V)	0-10
Output Current Range (mA)	4-20
Min. Ambient Temperature (°C)	0
Max. Ambient Temperature (°C)	55

#### Product Dimensions & Weight

Width (mm)	17,6
Height (mm)	90
Depth (mm)	89,5
Weight (kg)	0,1

#### Logistic Dimensions & Gross Weight

Length (cm)	11,0
Width (cm)	11,0
Height (cm)	5,0
Gross Weight (kg)	0,200
Volume (cdm)	0,605

#### Stock Data

Planned Delivery Time (Days)	58
------------------------------	----

#### Life Cycle

Sales Start	27.09.2005
Predecessor	151233 / FX2NC-4DA
Successor	<a href="#">169509 / FX3U-4DA</a>

#### Additional Product Information

Binding Tariff Information	DEBTI-40559/24-1
BTI validity date	01.12.2027
Battery included	NO

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO

RoHS Compliance	COMPLIANT
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,KR,LR,NK,RINA
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX3U-4DA-ADP&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX3U-4DA-ADP&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX3U-4DA-ADP&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX3U-4DA-ADP&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX3U-4DA-ADP&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX3U-4DA-ADP&amp;doc-lang=en</a>

### Product Packaging

Cardboard (g)	51
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

### Compatible products

Material	Description / Price List Text / Classification
<a href="#">149036</a>	TB-CON10-C PLC, FX Series Connector for Extension Modules, cage clamb connection 10 pin Class 100100111: FA-COM PLC: Other Option
<a href="#">221539</a>	TB-CON5-C PLC, FX Series Connector for ADP extension, cage clamb connection 5 pin Class 100100111: FA-COM PLC: Other Option