



## MATERIAL FACT SHEET

### 325715 FX5-4DA

#### General Data

Product Hierarchy	IAD21703
	Compact PLC
	FX5 Intelligent Unit
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_I/A/EUR/en/p/000000000000325715](https://mitsubishi-electric-eshop.mee.com/mee/FA_I/A/EUR/en/p/000000000000325715)

#### FA-COM PLC: Analogue I/O Module

Series	MELSEC IQ-F SERIES
Type	ANALOG OUTPUT
Power Supply (V)	24
Current Type	DC
Integrated Analogue Outputs	4
Output Voltage Range (V)	-10-10; 0-10; 0-5; 1-5
Output Current Range (mA)	0-20; 4-20
Min. Ambient Temperature (°C)	0
Max. Ambient Temperature (°C)	55

#### Product Dimensions & Weight

Width (mm)	40
Height (mm)	90
Depth (mm)	102,2
Weight (kg)	0,2

#### Logistic Dimensions & Gross Weight

Length (cm)	10,0
Width (cm)	12,5
Height (cm)	13,5
Gross Weight (kg)	0,263
Volume (cdm)	1,688

#### Stock Data

Planned Delivery Time (Days)	58
------------------------------	----

#### Life Cycle

Sales Start	01.01.2018
Predecessor	No Predecessor

#### Additional Product Information

Binding Tariff Information	DEBTI-40559/24-1
BTI validity date	01.12.2027
Battery included	NO

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT

WEEE	B2B
------	-----

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,LR,NK
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX5-4DA&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX5-4DA&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX5-4DA&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX5-4DA&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX5-4DA&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX5-4DA&amp;doc-lang=en</a>

### Product Packaging

Cardboard (g)	60
Other paper (g)	34
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

### Spare parts

Material	Description	Quantity	Unit
<a href="#">487742</a>	FX5-4AD/DA-ADP TERMINAL BLOCK	1	PC