

Search Automation Controls 🔍

Home Products Download Resource Support Sales Locations

Panasonic Industry > Automation Controls Top > FA Sensors & Components > Sensors > Inductive Proximity Sensors > GX-F8B

Sensors

Inductive Proximity Sensors >

Rectangular-shaped Inductive Proximity Sensor GX-F/H >

GX-F8B

Fiber Sensors >

Photoelectric Sensors / Laser Sensors >

Light Curtains / Safety Components >

Area Sensors >

Micro Photoelectric Sensors >

Particular Use Sensors >

Sensor Options >


Wire-Saving Systems >

Configuration examples of IO-Link compatible devices >

GX-F8B | Rectangular-shaped Inductive Proximity Sensor GX-F/H

Download

Catalog/
Datasheet CAD Manual



*Photo may vary from actual product.



?



Contact Us

Technical inquiries,
Purchase Support &
Additional Assistance

Technical inquiry

Business inquiry

Other inquiry

Product Number	GX-F8B
Part Number	GX-F8B
Product	Rectangular-shaped Inductive Proximity Sensor
Output details	NPN output
Product Name	Rectangular-shaped Inductive Proximity Sensor GX-F8B

Contact Us

Technical inquiry

Business inquiry

Other inquiry

Spec
Detail



Accessories
(Option)



As of April 26, 2025 (JST)
*Specifications and design of the products are subject to change without notice for the product improvement.

Spec Detail

Specifications and design of the products are subject to change without notice for the product improvement.

Item	Specifications
Product Number	GX-F8B
Part Number	GX-F8B
Products Name	Rectangular-shaped Inductive Proximity Sensor




Item	Specifications
Product details	NPN output
The price of the product	Please contact our office
Max. operation distance	2.5 mm 0.098 in plus or minus 8 % (Note) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
Stable sensing range	0 to 2.1 mm 0 to 0.083 in (Note) The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.
Standard sensing object	Iron sheet 15 × 15 × t 1 mm 0.591 × 0.591 × t 0.039 in
Applicable regulations and certifications	CE Marking (EMC Directive, RoHS Directive), UKCA Marking (EMC Regulations, RoHS Regulations)
Hysteresis	20 % or less of operation



Item	Specifications
	distance(with standard sensing object)
Repeatability	Along sensing axis, perpendicular to sensing axis: 0.04 mm 0.002 in or less
Supply voltage	12 to 24 V DC +10/-15 % Ripple P-P 10 % or less
Current consumption	15 mA or less
Output	NPN open-collector transistor - Maximum sink current: 100 mA - Applied voltage: 30 V DC or less (between output and 0 V) - Residual voltage: 2 V or less (at 100 mA sink current)
Output:Output operation	Normally closed
Output:Utilization category	DC-12 or DC-13
Max. response frequency	500 Hz
Operation indicator	Orange LED(lights up when the output is ON)
Protection	IP68 (IEC), IP68g (JEM) (Note) Panasonic Electric Works SUNX's IP68 test method 1. Immerse at 0 m below 0 °C +32 °F water surface



Item	Specifications
	<p>leave for 30 min. Then, immerse at 0 m below +70 °C +158 °F water surface and leave for 30 min.</p> <p>2. Regard the heat shock test in 1 as one cycle and perform 20 cycles.</p> <p>3. Leave in water at a depth of 1 m 3.281 ft in water for 500 hours.</p> <p>4. After tests 1 to 3, insulation resistance, voltage withstandability, current consumption, and sensing ranges must meet the standard values.</p> <p>(Note) If using the sensor in an environment where cutting oil droplets splatter, the sensor may be deteriorated due to added substances in the oil.</p>
Ambient temperature	-25 to +70 °C -13 to +158 °F , Storage: -40 to +85 °C - 40 to +185 ※
Ambient humidity	45 to 85 % RH, Storage: 35 to 95 % RH
Voltage withstandability	1,000 V AC for one min. between all supply termin  connected





Item	Specifications
	together and enclosure
Insulation resistance	50 MΩ , or more, with 500 V DC megger between all supply terminals connected together and enclosure
Vibration resistance	10 to 500 Hz frequency, 3 mm 0.118 in double amplitude (Max. 20 G) in X, Y and Z directions for two hours each
Shock resistance	10,000 m/s ² acceleration (1,000 G approx.) in X, Y and Z directions three times each
Sensing range variation:Temperature characteristics	Over ambient temperature range -25 to +70 °C -13 to +158degrees Fahrenheit: Within plus or minus 8 % of sensing range at +23 °C +73 °F
Sensing range variation:Voltage characteristics	Within plus or minus 2 % for +10/-15 % fluctuation of the supply voltage
Material	Enclosure: PBT Indicator part: Polycarbonate / Polyester



Item	Specifications
Cable	0.15 mm ² 3-core oil, heat and cold resistant cabtyre cable, 1 m 3.281 ft long
Cable extension	Extension up to total 100 m 328.084 ft is possible with 0.3 mm ² , or more, cable.
Net weight	15 g approx.

Accessories (Option)

	Product number	Part number	Product	D
	MS-GX8-1x10	MS-GX8-1x10	-	-
	MS-GXL8-4	MS-GXL8-4	-	-

Recently checked products

Recently checked product numbers

- GX-F8A-P | Rectangular-shaped Inductive Proximity Sensor GX-F/H

>
- GX-F8A | Rectangular-shaped Inductive Proximity Sensor GX-F/H

>
- GX-F15B-P | Rectangular-shaped Inductive Proximity Sensor GX-F/H

>



GX-F15B | Rectangular-shaped
Inductive Proximity Sensor GX-F/H

>

GX-F15A-P | Rectangular-shaped
Inductive Proximity Sensor GX-F/H

>

Contact Us

Control Components & Electronic Device Products Technical Support

Relays, Couplers,
Connectors, Switches,
and Other
Control Components &
Electronic Device
Products

Contact Us

FA Sensors & Components, Motors Technical Support

FA Sensors, PLC ,Eco
Power Meters, Times,
Counters, Limit Switches
and Other FA Sensors &
Components

Contact Us

Motors Technical Support

Motors for FA & Industrial
Application, Motors for
Appliance & Automotive

Contact Us

Guidelines for Ordering and Usage

Requests to customers (FA Sensors & Components [Excluding motors])

Requests to customers (Dedicated to industrial motors)



Components & Devices

Relays / Couplers
Connectors
Switches
Encoders / Potentiometers
Transparent Conductive Film
Cooling Fan

FA Sensors & Components

Fiber Sensors	Sensor Options	Static Control Devices
Photoelectric Sensors / Laser Sensors	Wire-Saving Systems	Laser Markers / 2D Code Readers
Micro Photoelectric Sensors	Programmable Controllers / Motion Controller	Machine Vision System
Light Curtains / Safety Components	Human Machine Interface	Energy Management Solutions
Area Sensors	Pressure Sensors / Flow Sensors	
Inductive Proximity Sensors	Measurement Sensors	
Particular Use Sensors		

Motors for FA & Industrial Application

AC Servo
Motors for HVAC & Automotive

