

JXD22B350 | US2:JXD22B350



SIEMENS LOW VOLTAGE SENTRON MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT, STANDARD 40 DEG C BREAKER JD FRAME WITH STANDARD BREAKING CAPACITY AND NON INTERCHANGEABLE TRIP. MEETS UL 489 / IEC 60947-2 STANDARDS. 350A 2-POLE BREAKER (65KAIC AT 240V). SPECIAL FEATURES: NO LUGS INSTALLED. DIMENSIONS (W x H x D) IN: 7.5 x 11 x 4.

List Price	Show prices
Customer Price	Show prices
Additional Services	For this product we can offer Services like Spare Part Delivery/Repair/Exchange. You have currently no rights to enter the Service Web Shop for that. For further information & to order this service, please contact your local Spares&Repair Partner
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	JXD22B350 US2:JXD22B350
Product Description	SIEMENS LOW VOLTAGE SENTRON MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT, STANDARD 40 DEG C BREAKER JD FRAME WITH STANDARD BREAKING CAPACITY AND NON INTERCHANGEABLE TRIP. MEETS UL 489 / IEC 60947-2 STANDARDS. 350A 2-POLE BREAKER (65KAIC AT 240V). SPECIAL FEATURES: NO LUGS INSTALLED. DIMENSIONS (W x H x D) IN: 7.5 x 11 x 4.
Product family	Not available
Product Lifecycle (PLM)	PM300:Active Product

Price data

Price Group	NIW
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	19 Day/Days
Net Weight (lb)	15.201 lb
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	783643212909
Commodity Code	8536200020
LKZ_FDB/ CatalogID	LV10.1
Product Group	3741
Group Code	P360
Country of origin	Mexico
Compliance with the substance restrictions according to RoHS directive	Since: 07/14/2008
Returnable	Yes
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	12	27-37-04-09
eClass	14	27-37-04-09
eClass	6	27-37-04-09
eClass	7.1	27-37-04-09
eClass	8	27-37-04-09
eClass	9	27-37-04-09
eClass	9.1	27-37-04-09
ETIM	7	EC000228
ETIM	8	EC000228

ETIM	9	EC000228
IDEA	4	4850
UNSPSC	15	39-12-16-01