


# Product datasheet

Specifications



## EasyPact TVS coil 110 VAC 50/60 Hz spare part for LC1E32...E38

LAEX2F7

### Main

|                                    |                         |
|------------------------------------|-------------------------|
| Range                              | Easy TeSys              |
| Range of product                   | Easy TeSys Control      |
| Product or component type          | Contacteur coil         |
| Device short name                  | LAEX                    |
| Product compatibility              | LC1E32...E38            |
| Accessory / separate part category | Spare parts             |
| Control circuit type               | AC at 50/60 Hz standard |
| [Uc] control circuit voltage       | 110 V AC 50/60 Hz       |
| Average resistance                 | 117 Ohm at 20 °C        |
| Inductance of closed circuit       | 4.07 H                  |

### Complementary

|                                 |  |
|---------------------------------|--|
| Control circuit voltage limits  | Operational: 0.85...1.1 Uc at 50/60 Hz (at <55 °C)                       |
| Inrush power in VA              | 70 VA 50/60 Hz cos phi 0.75 (at 20 °C)                                   |
| Hold-in power consumption in VA | 7 VA 50 Hz cos phi 0.3 (at 20 °C)<br>7.5 VA 60 Hz cos phi 0.3 (at 20 °C) |

### Environment

|                                       |            |
|---------------------------------------|------------|
| Ambient air temperature for operation | -5...55 °C |
| Net weight                            | 0.073 kg   |

### Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 3.8 cm |
| Package 1 Width              | 6.2 cm |
| Package 1 Length             | 7.8 cm |
| Package 1 Weight             | 71.0 g |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

|  |     |
|--|-----|
| Packaging made with recycled cardboard | Yes |
|--|-----|

|                                      |     |
|--------------------------------------|-----|
| Packaging without single use plastic | Yes |
|--------------------------------------|-----|

|                                   |           |
|-----------------------------------|-----------|
| <a href="#">EU RoHS Directive</a> | Compliant |
|-----------------------------------|-----------|

|                  |                                   |
|------------------|-----------------------------------|
| REACH Regulation | <a href="#">REACH Declaration</a> |
|------------------|-----------------------------------|

|                       |  |
|-----------------------|--|
| China RoHS Regulation | <a href="#">China RoHS declaration</a> |
|-----------------------|--|

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

No

---