Product datasheet

Specifications





High power contactor, TeSys Giga, 3 pole (3NO), AC-3 <=440V 225A, advanced version, 24...48V wide band AC/DC coil

LC1G225BEEA

Main

Mani		
Range	TeSys	
Range Of Product	TeSys Giga	
Product Or Component Type	Contactor	
Device Short Name	LC1G	
Contactor Application	Power switching Motor control	
Utilisation Category	AC-1 AC-3 AC-3e AC-4 AC-5a AC-5b AC-6a AC-6b AC-8a AC-8b DC-1 DC-3 DC-5	
Poles Description	3P	
[Ue] Rated Operational Voltage	<= 1000 V AC 50/60 Hz <= 460 V DC	
[le] Rated Operational Current	330 A (at <40 °C) at <= 1000 V AC-1 225 A (at <60 °C) at <= 440 V AC-3	
[Uc] Control Circuit Voltage	2448 V AC 50/60 Hz 2448 V DC	
Control Circuit Voltage Limits	Operational: 0.8 Uc Min1.1 Uc Max (at <60 °C) Drop-out: 0.1 Uc Max0.45 Uc Min (at <60 °C)	

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	330 A (at 40 °C)
Rated Breaking Capacity	2050 A at 440 V
[Icw] Rated Short-Time Withstand Current	1.8 kA - 10 s 1.0 kA - 30 s 0.85 kA - 1 min 0.56 kA - 3 min 0.44 kA - 10 min
Associated Fuse Rating	250 A aM at <= 440 V for motor

6 Jun 2024 Life Is On Schneider

400 A gG at <= 690 V

Average Impedance	0.00015 Ohm
[Ui] Rated Insulation Voltage	1000 V
Power Dissipation Per Pole	20 W AC-1 - Ith 330 A 8 W AC-3 - Ith 225 A
Compatibility Code	LC1G
Pole Contact Composition	3 NO
Auxiliary Contact Composition	1 NO + 1 NC
Motor Power Kw	55 kW at 230 V AC 50/60 Hz (AC-3e) 110 kW at 400 V AC 50/60 Hz (AC-3e) 110 kW at 415 V AC 50/60 Hz (AC-3e) 132 kW at 440 V AC 50/60 Hz (AC-3e) 132 kW at 500 V AC 50/60 Hz (AC-3e) 160 kW at 690 V AC 50/60 Hz (AC-3e) 132 kW at 1000 V AC 50/60 Hz (AC-3e) 132 kW at 1000 V AC 50/60 Hz (AC-3e) 55 kW at 230 V AC 50/60 Hz (AC-3) 110 kW at 400 V AC 50/60 Hz (AC-3) 110 kW at 415 V AC 50/60 Hz (AC-3) 132 kW at 150 V AC 50/60 Hz (AC-3) 132 kW at 500 V AC 50/60 Hz (AC-3) 132 kW at 690 V AC 50/60 Hz (AC-3) 132 kW at 400 V AC 50/60 Hz (AC-3) 132 kW at 1000 V AC 50/60 Hz (AC-3) 132 kW at 400 V AC 50/60 Hz (AC-3) 132 kW at 400 V AC 50/60 Hz (AC-3) 132 kW at 400 V AC 50/60 Hz (AC-4) 110 kW at 400 V AC 50/60 Hz (AC-4) 110 kW at 415 V AC 50/60 Hz (AC-4) 129 kW at 440 V AC 50/60 Hz (AC-4) 132 kW at 500 V AC 50/60 Hz (AC-4) 132 kW at 690 V AC 50/60 Hz (AC-4) 132 kW at 690 V AC 50/60 Hz (AC-4)
Motor Power Hp	60 hp at 200/208 V 60 Hz 75 hp at 230/240 V 60 Hz 150 hp at 460/480 V 60 Hz 150 hp at 575/600 V 60 Hz
Irms Rated Making Capacity	2720 A at 440 V
Coil Technology	Built-in bidirectional peak limiting
Mechanical Durability	8 Mcycles
Inrush Power In Va (50/60 Hz, Ac)	290 VA
Inrush Power In W (Dc)	220 W
Hold-In Power Consumption In Va (50/60 Hz, Ac)	10 VA
Hold-In Power Consumption In W (Dc)	5.7 W
Operating Time	4070 ms closing 1550 ms opening
Maximum Operating Rate	600 cyc/h AC-3 600 cyc/h AC-3e 300 cyc/h AC-1 150 cyc/h AC-4
Connections - Terminals	Power circuit: bar 2 - busbar cross section: 25 x 6 mm Power circuit: lugs-ring terminals 1 185 mm² Power circuit: bolted connection Control circuit: push-in 1 0.22.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.252.5 mm² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.51.0 mm² with cable end Control circuit: push-in 0.752.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.752.5 mm² - cable stiffness: flexible with cable end
Connection Pitch	35 mm
Mounting Support	Plate

Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1	
Product Certifications	CB Scheme CCC cULus EAC CE UKCA EU-RO-MR by DNV-GL	
Tightening Torque	18 N.m	
Height	255 mm	
Width	108 mm	
Depth	193 mm	
Net Weight	4.1 kg	

Environment

Ip Degree Of Protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
	1F2X HORE face with stributus combining to VDE 0100
Ambient Air Temperature For Operation	-2560 °C
Ambient Air Temperature For Storage	-6080 °C
Mechanical Robustness	Vibrations 5300 Hz 2 gn contactor open
	Vibrations 5300 Hz 4 gn contactor closed
	Shocks 10 gn 11 ms contactor open
	Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective Treatment	TH
Permissible Ambient Air Temperature Around The Device	-4070 °C at Uc

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	23.000 cm
Package 1 Width	25.000 cm
Package 1 Length	38.500 cm
Package 1 Weight	5.267 kg
Unit Type Of Package 2	S06
Number Of Units In Package 2	6
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	45.000 kg



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Mercury Free
Ø	Rohs Exemption Information Yes
⊘	Pvc Free
⊘	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

6 Jun 2024

Product datasheet

LC1G225BEEA

Installation

Installation Videos

TeSys Giga - How to install the auxiliary contact block

TeSys Giga - How to install and remove remote wear diagnosis module

TeSys Giga - How to install mechanical interlock kit

TeSys Giga - How to replace control module

TeSys Giga - How to replace switching modules

TeSys Giga - How to assemble reverser solution

TeSys Giga - How to assemble change-over solution

TeSys Giga - How to assemble star-delta starter solution New