

SIEMENS LOW VOLTAGE G FRAME CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. UL LISTED LGG FRAME WITH VERY HIGH BREAKING CAPACITY. 40A 3-POLE (14KAIC AT 600Y/347V) (65KAIC AT 480V). SPECIAL FEATURES: LINE AND LOAD SIDE LUGS (TC1G20) WIRE RANGE: 8 - 1/0 AWS (CU/AL). DIMENSIONS (W X H X D) IN: 3 x 5.4 x 2.8.

Image similar

Article Number (Market Facing Number)	LGG3B040L US2:LGG3B040L
Product Description	SIEMENS LOW VOLTAGE G FRAME CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. UL LISTED LGG FRAME WITH VERY HIGH BREAKING CAPACITY, 40A 3-POLE (14KAIC AT 600V/347V) (65KAIC AT 480V). SPECIAL FEATURES: LINE AND LOAD SIDE LUGS (TC1GG20) WIRE RANGE: 8 - 1/0 AWS (CU/AL). DIMENSIONS (W x H x D) IN: 3 x 5.4 x 2.8.
Product family	Ordering Data Overview
Product Lifecycle (PLM)	PM300:Active Product

Price Group	ND4
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	19 Day/Days
Net Weight (lb)	2,756 lb
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

EAN	Not available
UPC	887621279202
Commodity Code	8536200020
LKZ_FDB/ CatalogID	LV10.1
Product Group	5362
Group Code	P360
Country of origin	Mexico
Compliance with the substance restrictions according to RoHS directive	not available
Returnable	No
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

	Version	Classification
eClass	12	27-37-04-09
eClass	14	27-37-04-09
eClass	6	27-37-04-09
eClass	7.1	27-37-04-09
eClass	8	27-37-04-09
eClass	9	27-37-04-09
eClass	9.1	27-37-04-09
ETIM	7	EC000228
ETIM	8	EC000228
ETIM	9	EC000228
IDEA	4	4850
UNSPSC	15	39-12-16-01

;