

# Product datasheet

Specifications



## trip unit accessory - SDTAM 24/415V AC/DC - for NSX100..250 / NSX400..630

LV429424

### Main

Range of product	ComPact NSX100...250 ComPact NSX400...630
Range	ComPact
Device short name	SDTAM
Product or component type	Thermal fault module
Device application	Signalling
Range compatibility	ComPact ComPact NSX circuit breaker
Accessory / separate part category	Trip unit accessory
Trip unit name	MicroLogic 2.3 M MicroLogic 2.2 M MicroLogic 6.3 E-M MicroLogic 6.2 E-M

### Complementary

Maximum output current	0.08 A
[Us] rated supply voltage	24...415 V AC 50/60 Hz 24...415 V DC

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	5.0 cm
Package 1 Length	10.5 cm
Package 1 Weight	58.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	46
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.123 kg

Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)