

Product datasheet

Specifications



short terminal shield, Compact NSX,
EasyPact CVS, 4 poles, pitch 35
mm

LV429516

Main

Product or component type	Short terminal shield
Range compatibility	ComPacT new generation ComPacT NSX100 new generation ComPacT new generation ComPacT NSX160 new generation ComPacT new generation ComPacT NSX250 new generation ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPact NSX250 ComPacT new generation ComPacT NSX DC new generation NSX100 DC ComPacT new generation ComPacT NSX DC new generation NSX160 DC ComPacT new generation ComPacT NSX DC new generation NSX250 DC ComPact Compact NSX100 DC ComPact Compact NSX160 DC ComPact Compact NSX250 DC EasyPact EasyPact CVS100 EasyPact EasyPact CVS160 EasyPact EasyPact CVS250
Accessory / separate part type	Insulation accessories
Poles description	4P
Quantity per set	1

Complementary

Connection pitch	35 mm
IP degree of protection	IP40 conforming to IEC 60529
Product compatibility	Circuit-breaker Plug-in base

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	15.800 cm
Package 1 Length	16.500 cm
Package 1 Weight	73.500 g
Unit Type of Package 2	S04
Number of Units in Package 2	40
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm

Package 2 Length	60.000 cm
Package 2 Weight	3.842 kg
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	50.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	27.368 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)