

# Product datasheet

Specifications



## Vigi add-on alarm module, Compact NSX 400/630, 200 VAC to 440 VAC, 0.1 A to 1 A, 3 poles

LV432659

⚠ Discontinued on: 01 November 2020

⚠ Discontinued

### Main

Product or component type	Insulation monitoring device
Device application	Insulation
Range compatibility	ComPact ComPact NSX400 ComPact ComPact NSX630
Poles description	3P

### Complementary

[Ue] rated operational voltage	200...440 V
Network type	AC
Network frequency	50/60 Hz
Measurement accuracy	-50 %...0 %
Residual earth-leakage sensivity adjustment type	Adjustable
[IΔn] residual earth-leakage sensitive adjustment	0.1 A 0.2 A 0.5 A 1 A
[Δt] residual earth-leakage time delay adjustment	5...10 s

### Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.5 cm
Package 1 Width	17 cm
Package 1 Length	20 cm
Package 1 Weight	2.65 kg

Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)