Product data sheet

Specifications



() Discontinued

Main

Range of product

70A 2P NB STAB-LOK MOULDED CASE CIRCUIT BREAKER 10KA

NB270

Stab-lok

() Discontinued on: Jan 18, 2022

Product or component type Miniature circuit-breaker Complementary [In] rated current 70 A [Ue] rated operational voltage 120/240 V AC Mounting mode Bolt-on Poles description 2P Breaking capacity 10 kA Electrical connection Screw connector AWG gauge AWG 14...AWG 2 aluminum/copper AWG 4...AWG 2/0 aluminum/copper

Environment

Product certifications

CSA

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.00 in (7.62 cm)
Package 1 Width	2.00 in (5.08 cm)
Package 1 Length	3.40 in (8.636 cm)
Package 1 Weight	10.240 oz (290.299 g)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

```
How we assess product sustainability \geq
```

Use Better

Materials and Substances		
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	China RoHS declaration	