

# Product data sheet

Specifications



## 15A 1P GROUND FAULT NB 5MA MOULDED CASE CIRCUIT

NBGF15

⚠ Discontinued on: May 12, 2023

⚠ Discontinued

### Main

Range of product	Stab-lok
Product or component type	Miniature circuit-breaker

### Complementary

[In] rated current	15 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Bolt-on
Poles description	1P
Electrical connection	Screw connector
AWG gauge	AWG 14...AWG 8 aluminum/copper
Protection type	Ground fault protection
Short-circuit protection	5 A

### Environment

Product certifications	CSA
------------------------	-----

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.10 in (7.874 cm)
Package 1 Width	2.00 in (5.08 cm)
Package 1 Length	4.50 in (11.43 cm)
Package 1 Weight	8.160 oz (231.332 g)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
EU RoHS Directive	<a href="#">Compliant with Exemptions</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>