

Specifications



Photo is representative



Eaton QCR2020HT

Eaton Quicklag Type QCR 1/2-inch Industrial Thermal-Magnetic Circuit Breaker, Industrial circuit breaker, Rear mounting, 20 A, 10 kAIC, Two-pole, 240 V, Thermal-magnetic, Cable-in/cable-out, QCR, Ring or spade lug terminals

General specifications

PRODUCT NAME	Eaton QCR thermal magnetic circuit breaker
CATALOG NUMBER	QCR2020HT
UPC	782114225851
PRODUCT LENGTH/DEPTH	5.75 in
PRODUCT HEIGHT	3.5 in
PRODUCT WIDTH	2 in
PRODUCT WEIGHT	0.5 lb
WARRANTY	1 year
COMPLIANCES	HACR Rated
CERTIFICATIONS	CSA Certified UL Listed
CATALOG NOTES	Standard breaker terminals are box type lugs. Suitable for line and load side ring terminal connection (#10-32 plus/minus terminal screw provided).



Powering Business Worldwide

Physical Attributes	
CIRCUIT BREAKER TYPE	QCR
CONNECTION	Cable-in/cable-out
MOUNTING METHOD	Rear
NUMBER OF POLES	Two-pole
TERMINALS	Ring or spade lug
TYPE	Industrial circuit breaker

Performance Ratings	
AMPERAGE RATING	20 A
INTERRUPT RATING	10 kAIC
TRIP TYPE	T268
VOLTAGE RATING	240 V - 240 V

Miscellaneous	
APPLICATION	Rear mounting
SPECIAL FEATURES	Ring or Spade Lug Terminals

Resources	
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - QCR2020HT

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. Follow us on social media to get the latest product and support information.
All other trademarks are property of their respective owners.

