

Product data sheet

Specifications

SQUARE D



[TAA] Mini circuit breaker, QO, 15A, 1 pole, 120VAC, 10kA, plug in, combo ARC fault, plug on neutral

QO115PCAFI

⚠ Discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	15 A
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Combination ARC-fault
Ratings	HACR rated
Electrical Connection	Pressure plate
Connections Terminals	Plug-on neutral

Complementary

Interrupt Rating	10 kA 120 V AC
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening Torque	35.4 lbf.in (4 N.m)
Height	4.8 in (121 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Product Weight	0.500 lb(US) (0.227 kg)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A06303
Discount Schedule	DE2A
GTIN	785901062615
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin	MX
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	1.00 in (2.54 cm)
------------------	-------------------

Package 1 Width	3.80 in (9.652 cm)
-----------------	--------------------

Package 1 Length	4.90 in (12.446 cm)
------------------	---------------------

Package 1 Weight	8.000 oz (226.796 g)
------------------	----------------------

Unit Type of Package 2	CAR
------------------------	-----

Number of Units in Package 2	52
------------------------------	----

Package 2 Height	3.80 in (9.652 cm)
------------------	--------------------

Package 2 Width	13.90 in (35.306 cm)
-----------------	----------------------

Package 2 Length	20.80 in (52.832 cm)
------------------	----------------------

Package 2 Weight	26.601 lb(US) (12.066 kg)
------------------	---------------------------

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 39

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

China RoHS Regulation [China RoHS declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No