



Mini circuit breaker, QO, 125A, 2 pole, 120/240VAC, 22kA, plug in

QO2125VH

Product availability: Stock - Normally stocked in distribution facility

Price*: 1,034.00 USD

Main

| Product | Miniature circuit-breaker | |
|-----------------------|---------------------------|--|
| Range | QO | |
| Current Rating | 125 A | |
| Voltage Rating | 120/240 V AC 120 V AC | |
| Mounting Type | Plug-in | |
| Number of Poles | 2P | |
| Circuit Breaker Type | Standard | |
| Ratings | HACR rated | |
| Electrical Connection | Box lugs | |

Complementary

| Interrupt Rating | 22 kA 120/240 V AC 22 kA 120 V AC | |
|------------------------|--------------------------------------|--|
| Number of Panel Spaces | 2 | |
| Wire Size | AWG 4AWG 2/0 copper or aluminium | |
| Tightening Torque | 49.6 lbf.in (5.6 N.m) | |
| Height | 3.5 in (89 mm) | |
| Width | 1.5 in (38 mm) | |
| Depth | 2.9 in (74 mm) | |
| Product Weight | 0.701 lb(US) (0.318 kg) | |

Environment

| Certifications | UL Listed CSA |
|----------------|------------------|
| Ambient Rating | 104 °F (40 °C) |

Ordering and shipping details

| Category | US1DE2A00926 | | |
|-------------------|--------------|--|--|
| Discount Schedule | DE2A | | |
| GTIN | 785901054948 | | |
| Returnability | Yes | | |
| Country of origin | US | | |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|---------------------------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 1.60 in (4.064 cm) | |
| Package 1 Width | 3.30 in (8.382 cm) | |
| Package 1 Length | 3.80 in (9.652 cm) | |
| Package 1 Weight | 11.520 oz (326.586 g) | |
| Unit Type of Package 2 | CAR | |
| Number of Units in Package 2 | 51 | |
| Package 2 Height | 3.90 in (9.906 cm) | |
| Package 2 Width | 14.00 in (35.560 cm) | |
| Package 2 Length | 21.00 in (53.340 cm) | |
| Package 2 Weight | 36.350 lb(US) (16.488 kg) | |

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint | |
|--|-------------------------------|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 19 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Packaging made with recycled cardboard | No |
|--|---|
| Packaging without single use plastic | Yes |
| SCIP Number | Af42fb01-813d-40c0-ae28-b8b3299dbc99 |
| China RoHS Regulation | China RoHS declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Use Again

| ○ Repack and remanufacture | |
|-----------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Halogen content performance | Halogen free product |
| Take-back | No |