

# Product data sheet

Specifications

SQUARE D



Mini circuit breaker, QO, 10A, 2 pole, 120/240VAC, 10kA, bolt on

QOB210

## Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	10 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate

## Complementary

Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC
Number of Panel Spaces	2
Wire Size	AWG 14...AWG 8 copper or aluminum
Tightening Torque	35.4 lbf.in (4 N.m)
Height	3.0 in (76 mm)
Width	1.5 in (38 mm)
Depth	2.9 in (74 mm)
Product weight	0.560 lb(US) (0.254 kg)

## Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.50 in (3.810 cm)
Package 1 Width	3.50 in (8.890 cm)
Package 1 Length	3.50 in (8.890 cm)

<b>Package 1 Weight</b>	8.960 oz (254.012 g)
<b>Unit Type of Package 2</b>	CAR
<b>Number of Units in Package 2</b>	43
<b>Package 2 Height</b>	3.80 in (9.652 cm)
<b>Package 2 Width</b>	13.00 in (33.020 cm)
<b>Package 2 Length</b>	20.50 in (52.070 cm)
<b>Package 2 Weight</b>	24.661 lb(US) (11.186 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **19**

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **Yes**

SCIP Number **Af42fb01-813d-40c0-ae28-b8b3299dbc99**

China RoHS Regulation [China RoHS declaration](#)

### Use Again

#### Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Halogen content performance **Halogen free product**

Take-back **No**