

# Product data sheet

Specifications

**SQUARE D**



Mini circuit breaker, QO, 150A, 3 pole, 120/240VAC, 22kA, bolt on

QOB3150VH

## Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	150 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	Not rated
Electrical Connection	Box lugs

## Complementary

Interrupt Rating	22 kA 120/240 V AC 22 kA 240 V AC 22 kA 120 V AC
Number of Panel Spaces	6
Wire Size	AWG 4...300 kcmil copper or aluminum
Tightening Torque	250.5 lbf.in (28.3 N.m)
Height	5.7 in (145 mm)
Width	4.5 in (114 mm)
Depth	4.9 in (124 mm)
Product weight	0.549 lb(US) (0.249 kg)

## Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.30 in (10.922 cm)
Package 1 Width	5.00 in (12.700 cm)

<b>Package 1 Length</b>	6.70 in (17.018 cm)
<b>Package 1 Weight</b>	3.979 lb(US) (1.805 kg)
<b>Unit Type of Package 2</b>	PAL
<b>Number of Units in Package 2</b>	558
<b>Package 2 Height</b>	40.00 in (101.600 cm)
<b>Package 2 Width</b>	40.00 in (101.600 cm)
<b>Package 2 Length</b>	48.00 in (121.920 cm)
<b>Package 2 Weight</b>	2199.0004 lb(US) (997.449 kg)

## **Contractual warranty**

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **28**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **Yes**

SCIP Number **Af42fb01-813d-40c0-ae28-b8b3299dbc99**

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Halogen content performance **Halogen free product**

Take-back **No**