SQUARE D



Mini circuit breaker, QOU, 10A, 2 pole, 120/240VAC, 10kA

QOU210

Product availability: Stock - Normally stocked in distribution facility

Price*: 92.46 USD

Main

Product or Component Type	Miniature circuit-breaker	
Range of Product	QOU	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	

Complementary

Line Rated Current	10 A	
Electrical connection	Slotted box lugs, line side	
	Slotted box lugs, load side	
[Ue] rated operational voltage	120/240 V AC	
	120 V AC	
	48 V DC	
Mounting Mode	Unit mount	
AWG gauge	AWG 14AWG 2 aluminium/copper	
Height	4.45 in (113.03 mm)	
Width	1.5 in (38.1 mm)	
Depth	2.95 in (74.93 mm)	
Tightening torque	45 lbf.in (5.08 N.m) (AWG 14AWG 2)	

Environment

Product Certifications	CSA IEC
	UL Listed

Ordering and shipping details

Category	US10DE200900
Discount Schedule	0DE2
GTIN	785901477457
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	2.10 in (5.334 cm)	
Package 1 Width	3.50 in (8.89 cm)	
Package 1 Length	4.80 in (12.192 cm)	
Package 1 Weight	11.840 oz (335.658 g)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	19
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product
Take-back	No