



## MATERIAL FACT SHEET

### 279557 R60DA4

#### General Data

Product Hierarchy	IAD51401
	Modular PLC
	IQ-R Standard
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/0000000000000279557](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/0000000000000279557)

#### FA-MOD PLC: Analogue I/O Module

Series	MELSEC IQ-R SERIES
Type	ANALOG OUTPUT
Power Supply (V)	24
Current Type	DC
Occupied I/O Points on PLC	16
Integrated Analogue Outputs	4
Output Voltage Range (V)	-10-10; 0-5; 1-5
Output Current Range (mA)	0-20; 4-20
Wiring	SCREW
Int. Current Consumption (A)	0,16

#### Product Dimensions & Weight

Width (mm)	27,8
Height (mm)	106
Depth (mm)	131
Weight (kg)	0,14

#### Logistic Dimensions & Gross Weight

Length (cm)	15,0
Width (cm)	5,0
Height (cm)	16,5
Gross Weight (kg)	0,263
Volume (cdm)	1,238

#### Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

#### Life Cycle

Sales Start	09.12.2014
Predecessor	No Predecessor

#### Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	<a href="#">2451-62-9</a>
REACH Substance CAS Number (2)	<a href="#">68-12-2</a>

REACH Substance CAS Number (3)	<a href="#">7439-92-1</a>
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

#### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,LR,NK,RINA
UKCA	COMPLIANT

#### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=R60DA4&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=R60DA4&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=R60DA4&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=R60DA4&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=R60DA4&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=R60DA4&amp;doc-lang=en</a>

#### Product Packaging

Cardboard (g)	45
Other paper (g)	26
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3
Wood (g)	0
Glass (g)	0
Others (g)	0

#### Compatible products

Material	Description / Price List Text / Classification
<a href="#">249089</a>	Q6TE-18SN PLC Q Series Spring/tension clamp Frontunit for 16-point I/O modules Class 100100215: FA-MOD PLC: Other Option