

# Product datasheet

Specifications



## Buzzer, Unica pure, 70dB, 1 module, IP41, grey

UNSBUZZER1M\_GY

### Main

Range	Unica Pure
Product or component type	Buzzer
device presentation	Mechanism
[Ue] rated operational voltage	220 V
Number of modules	1 module
Fixing mode	Snap-in
Colour tint	Grey
Main colour tint	Grey

### Complementary

Device mounting	Flush
Operating time	60 s
Noise level	70 dB
Cable cross section	1.5...2.5 mm² flexible cable 1.5...2.5 mm² rigid or stranded cable
Material	ABS (acrylonitrile butadiene-styrene): front cover PC (polycarbonate) GF10 FR: back cover
Standards	IEC 62080
Ambient air temperature for operation	-5...35 °C
Depth	53 mm
Width	22.5 mm
Height	45 mm
Net weight	0.037 kg

### Environment

IK degree of protection	IK04
IP degree of protection	IP41

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.8 cm
Package 1 Width	4.2 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	9.6 cm
Package 1 Weight	40 g