

Product data sheet

Specifications



Control station, Harmony eXLhoist, standard, XARS8L12W system with charger, shoulder belt, cable USB RJ45 and config software

XARSK8L12W

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1,450.00 USD

Main

| | |
|------------------------------|--|
| Range of Product | Harmony eXLhoist |
| Product or Component Type | Control station |
| Device short name | XARS |
| Control station type | Wireless |
| Product Specific Application | Material handling Hoisting applications |
| Number of Channels | 50 |
| Control station application | Stop function SIL 2 maximum can reach PL d/category 3)IEC 62061 Stop function SIL 2 maximum can reach PL d/category 3)ISO 13849-1 Emergency stop function SIL 3 maximum can reach PL e/category 4)IEC 62061 Emergency stop function SIL 3 maximum can reach PL e/category 4)ISO 13849-1 Motion function SIL 1 maximum can reach PL c/category 1)IEC 62061 Motion function SIL 1 maximum can reach PL c/category 1)ISO 13849-1 Limiter protection function SIL 1 maximum can reach PL c/category 1)IEC 62061 Limiter protection function SIL 1 maximum can reach PL c/category 1)ISO 13849-1 |

Complementary

| | |
|----------------------------|--|
| Kit composition | Cable Remote control Shoulder belt Base station Configuration software |
| Operating distance | 100 m in free air |
| Cable entry | Cable gland |
| Communication network type | Wireless bluetooth low energy |
| Transmission frequency | 2.4 GHz |

Environment

| | |
|-------------------|---|
| Radio agreement | SRRC ICASA FCC ARIB RSS ANATEL |
| Relative humidity | 0...95 % -4...113 °F (-20...45 °C) storage |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------------|---|
| Electromagnetic compatibility | Resistance to electrostatic discharge - test level: 4 kV class B (on contact) conforming to IEC 61000-4-2 Resistance to electrostatic discharge - test level: 8 kV class B (in air) conforming to IEC 61000-4-2 Resistance to radiated electromagnetic fields - test level: 10 V/m class B conforming to IEC 61000-4-3 |
| Standards | IEC 60204-1 safety ISO 13849-1 safety IEC 62061 safety IEC 61508 safety ISO 13850 safety IEC 60204-32 hoisting applications ETSI EN 301 489-1 radio ETSI EN 301 489-3 radio ETSI EN 301 489-17 radio ETSI EN 300 440-2 radio ETSI EN 300 328 radio FCC part 15 radio RSS GEN issue 3 radio RSS 210 issue 8 radio ARIB STD-T81 radio |
| Product certifications | CE UL CSA C-tick JIS KC EAC |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10CS222479 |
| Discount Schedule | 0CS2 |
| GTIN | 3606480662393 |
| Returnability | Yes |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.874 in (20.000 cm) |
| Package 1 Width | 11.220 in (28.500 cm) |
| Package 1 Length | 12.087 in (30.700 cm) |
| Package 1 Weight | 6.678 lb(US) (3.029 kg) |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 11.811 in (30.000 cm) |
| Package 2 Width | 15.748 in (40.000 cm) |
| Package 2 Length | 23.622 in (60.000 cm) |
| Package 2 Weight | 14.551 lb(US) (6.600 kg) |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

| | |
|-------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
|-------------------|--|

| | |
|-----------------------|--|
| China Rohs Regulation | China RoHS declaration |
|-----------------------|--|

| | |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile |
|--------------------------|---|

| | |
|------|--|
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
|------|--|

| | |
|---------------------|---|
| Circularity Profile | End of Life Information |
|---------------------|---|

| | |
|---------------------------|---|
| California Proposition 65 | "WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov " |
|---------------------------|---|

Image of product / Alternate images

Alternative





