



# indicator bank with buzzer + 3 illuminated units Ø 45 mm - 230 V AC

XVMM2RAGSB

# Main

Range of product	Harmony XVM	
Product or component type	Pre-assembled and pre-cabled indicator bank	
Beacon or indicator bank unit type	3 illuminated units	
Component name	XVM	
Light source	Green super bright LED with BA 15d base steady signalling Orange super bright LED with BA 15d base steady signalling Red super bright LED with BA 15d base steady signalling	
Light block color	Red/orange/green	
[Us] rated supply voltage	230 V AC	
Indicator bank base type	Base without buzzer	
Mounting mode	Vertical	

# Complementary

Kit composition	Aluminium support tube Plastic fixing plate Base unit Cover	
Mounting diameter	45 mm	
Connections - terminals	Flying leads,clamping capacity: 1 x 0.325 mm² (AWG 22)	
Marking	CE	
Mounting support	Aluminium tube	
Short-circuit protection	0.2 A	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
Current consumption	15 mA on steady LED unit	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	
Net weight	0.443 kg	

## **Environment**

IP degree of protection	IP42 vertical position conforming to IEC 60529	
Product certifications	ccc	
Standards	IEC 60947-1 IEC 60947-5-1	
Ambient air temperature for storage	-2570 °C	

Ambient air temperature for operation	-1050 °C
Overvoltage category	Class I conforming to IEC 60947-1 Class I conforming to IEC 60947-5-1 Class I conforming to IEC 61140
Protective treatment	TC

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	8.5 cm
Package 1 Length	54 cm
Package 1 Weight	585 g
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	13 kg
Unit Type of Package 3	P06
Number of Units in Package 3	80
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	60 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance



Mercury Free



Rohs Exemption Information

Yes

## **Certifications & Standards**

Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Circularity Profile	No need of specific recycling operations	


# XVMM2RAGSB

#### **Dimensions Drawings**

Pre-Assembled and Pre-Cabled Tower Light with Fixing Base for Mounting on Vertical Support (Support Tube + Metal Bracket)

#### **Dimensions**

Below drawing shows the maximum configuration of the product. Select the number of stages according to the product characteristics in order to get **b2** dimension.



#### (1) Base unit with or without buzzer.

Number of illuminated units	b2 in mm	b2 in in.
1 unit	383	15.08
2 units	448	17.64
3 units	513	20.20
4 units	578	22.76

Product datasheet XVMM2RAGSB

# **Product datasheet**

## XVMM2RAGSB

#### Connections and Schema

#### **Pre-Assembled and Pre-Cabled Tower Light**

#### **Wire Colors**

4th illuminated unit: yellow wire 3rd illuminated unit: green wire 2nd illuminated unit: white wire 1st illuminated unit: blue wire

Common: black wire

Buzzer (if integrated in base unit): grey wire